



Ampère	Poles	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	> 50 - 500 V 100 - 300 Hz	> 50 - 500 V over 300 - 500 Hz		
		3pole 4h, 4pole 4h, 5pole 4h	3pole 6h, 4pole 9h, 5pole 9h	3pole 9h, 4pole 6h, 5pole 6h	3pole 7h, 4pole 7h, 5pole 7h	3pole 10h, 4pole 10h, 5pole 10h	3pole 2h, 4pole 2h, 5pole 2h		

Part numbers


	16	3	411 304	411 306	411 309				10	128	
	16	4	410 404	410 409	410 406	410 407	410 410	410 402	10	160	
	16	5	410 504	410 509	410				10	165	
	16	5			410 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)						
	32	3	430 304	430 306	430 309				10	208	
	32	4	430 404	430 409	430 406	430 407	430 410	430 402	10	215	
	32	5	430 504	430 509	430				10	226	
32	5			430 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)							
Panel sockets straight IP 44, fingerproof acc. to BGV A2											
	63	3	460 304	460 306	460 309				5	586	
	63	4	460 404	460 409	460 406	460 407	460 410	460 402	5	645	
	63	5	460 504	460 509	460				5	776	
	63	5			460 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)						
Panel sockets straight IP 44, fingerproof acc. to BGV A2											
	16	4	411 404	411 409	411 406	411 407	411 410	411 402	10	200	
	16	5	411 504	411 509	411				10	218	
	32	3	431 304	431 306	431 309				10	223	
	32	4	431 404	431 409	431 406	431 407	431 410	431 402	10	230	
32	5	431 504	431 509	431				10	283		
Panel sockets straight IP 44, fingerproof acc. to BGV A2, flange screwed on											
	16	3	410 304	410 306	410 309				10/60	117	
	16	3	412 304	412 306	412 309 (flange screwed on)				10	129	
Panel sockets straight IP 44 , fingerproof acc. to BGV A2											
	16	3	415 304	415 306	415 309				10	200	
	16	4	415 404	415 409	415 406	415 407	415 410	415 402	10	214	
	16	5	415 504	415 509	415				10	263	
	32	3	435 304	435 306	435 309				10	265	
	32	4	435 404	435 409	435 406	435 407	435 410	435 402	10	271	
	32	5	435 504	435 509	435				10	276	
mondo panel sockets straight IP 44 , RAL 7035 light grey											
	16	3	417 304	417 306	417 309				10	153	
	mondo panel sockets IP 44 , also for installation channel, RAL 7035 light grey										
	16	2		10 003 (blue)					10	46	
	16	2		10 001 (grey)					10	46	
	16	2		10 014 (protection against accidental contact acc. to BGV A2 for Schuko sockets)							
	16	2		10 005 (blue, with extra flange)					10	70	
16	2		10 006 (grey, with extra flange)					10	70		
fixing dimensions = 60 x 60 mm / flange dimensions = 75 x 75 mm											
Earthing contact socket IP 44 , panel socket straight											
	16	2		10 004					10	94	
	Earthing contact socket IP 44 , mondo panel sockets straight, RAL 7035 light grey										





Ampère	Poles	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	> 50 - 500 V 100 - 300 Hz	> 50 - 500 V over 300 - 500 Hz
		3pole 4h, 4pole 4h, 5pole 4h	3pole 6h, 4pole 9h, 5pole 9h	3pole 9h, 4pole 6h, 5pole 6h	3pole 7h, 4pole 7h, 5pole 7h	3pole 10h, 4pole 10h, 5pole 10h	3pole 2h, 4pole 2h, 5pole 2h





Part numbers

	16	3	510 304	510 306	510 309				10	120
	16	4	510 404	510 409	510 406	510 407	510 410	510 402	10	160
	16	5	510 504	510 509	510				10	175
	510 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)									
	32	3	530 304	530 306	530 309				10	207
	32	4	530 404	530 409	530 406	530 407	530 410	530 402	10	216
	32	5	530 504	530 509	530				10	240
	530 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)									


530 **Panel sockets angled IP 44 , fingerproof acc. to BGV A2**


	16	4	511 404	511 409	511 406	511 407	511 410	511 402	10	181
	16	5	511 504	511 509	511				10	201
	32	3	531 304	531 306	531 309				10	218
	32	4	531 404	531 409	531 406	531 407	531 410	531 402	10	236
	32	5	531 504	531 509	531				10	254
	63	3	560 304	560 306	560 309				5	593
	63	4	560 404	560 409	560 406	560 407	560 410	560 402	5	677
	63	5	560 504	560 509	560				5	708
	560 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)									


531 **Panel sockets angled IP 44 , fingerproof acc. to BGV A2**


	16	5	512 504	512 509	512				10	198
	512 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)									
	32	5	532 504	532 509	532				10	259
	532 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)									
	63	5	562 504	562 509	562				5	715
	562 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)									


532 **Panel sockets angled IP 44 , 16 - 63 A fingerproof acc. to BGV A2**

	16	3	514 304	514 306	514 309				10	158
	16	4	514 404	514 409	514 406	514 407	514 410	514 402	10	202
	16	5	514 504	514 509	514				10	220
	32	3	534 304	534 306	534 309				10	300
	32	4	534 404	534 409	534 406	534 407	534 410	534 402	10	285
	32	5	534 504	534 509	534				10	305

534 **Panel sockets angled IP 44 , flange screwed on**

	63	3	564 304	564 306	564 309				5	646
	63	4	564 404	564 409	564 406				5	695
	63	5	564 504	564 509	564				5	744

564 **Panel sockets angled IP 44 , flange screwed on**

	16	3	512 304	512 306	512 309				10	120
---	----	---	---------	----------------	---------	--	--	--	----	-----

512 306 **Panel sockets angled IP 44 , with eyehook for padlock**



Ampère	Poles	110 V 50 a. 60 Hz			230 V 50 a. 60 Hz			400 V 50 a. 60 Hz			500 V 50 a. 60 Hz			> 50 - 500 V 100 - 300 Hz			> 50 - 500 V over 300 - 500 Hz				
		3pole 4h	4pole 4h	5pole 4h	3pole 6h	4pole 9h	5pole 9h	3pole 9h	4pole 6h	5pole 6h	3pole 7h	4pole 7h	5pole 7h	3pole 10h	4pole 10h	5pole 10h	3pole 2h	4pole 2h	5pole 2h		

Part numbers

	16	3	419 304	419 306	419 309					10	139		
	16	4	419 404	419 409	419 406	419 407	419 410	419 402	10	186			
	16	5	419 504	419 509	419				10	202			
	16	5	419 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)										
	32	3	439 304	439 306	439 309					10	246		
	32	4	439 404	439 409	439 406	439 407	439 410	439 402	10	252			
	32	5	439 504	439 509	439				10	278			
	32	5	439 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)										
	63	3	469 304	469 306	469 309					5	599		
	63	4	469 404	469 409	469 406	469 407	469 410	469 402	5	699			
	63	5	469 504	469 509	469				5	799			
	63	5	469 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)										

439 Panel sockets straight IP 67, fingerproof acc. to BGV A2

	125	3	479 304	479 306	479 309					2	990
	125	4	479 404	479 409	479 406	479 407	479 410	479 402	2	1155	
	125	5	479 504	479 509	479				2	1319	

479 Panel sockets straight IP 67, with multi contact, fingerproof acc. to BGV A2

	16	3	519 304	519 306	519 309					10	142		
	16	4	519 404	519 409	519 406	519 407	519 410	519 402	10	257			
	16	5	519 504	519 509	519				10	223			
	16	5	519 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)										
	32	3	539 304	539 306	539 309					10	263		
	32	4	539 404	539 409	539 406	539 407	539 410	539 402	10	287			
	32	5	539 504	539 509	539				10	303			
	32	5	539 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)										
	63	3	569 304	569 306	569 309					5	638		
	63	4	569 404	569 409	569 406	569 407	569 410	569 402	5	725			
	63	5	569 504	569 509	569				5	832			
	63	5	569 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)										

519 Panel sockets angled IP 67, fingerproof acc. to BGV A2

	125	3	579 304	579 306	579 309					2	988
	125	4	579 404	579 409	579 406	579 407	579 410	579 402	2	1152	
	125	5	579 504	579 509	579				10	22	

579 Panel sockets angled IP 67, with multi contact, fingerproof acc. to BGV A2

	16	4	517 404	517 409	517 406	517 407	517 410	517 402	10	194
	16	5	517 504	517 509	517				10	212
	32	3	537 304	537 306	537 309				10	255
	32	4	537 404	537 409	537 406	537 407	537 410	537 402	10	273
	32	5	537 504	537 509	537				10	293
	63	5	567 504	567 509	567				5	843

517 Panel sockets angled IP 67, fingerproof acc. to BGV A2

	16	3	518 304	518 306	518 309					10	238
	16	4	518 404	518 409	518 406	518 407	518 410	518 402	10	256	
	16	5	518 504	518 509	518				10	274	
	32	3	538 304	538 306	538 309				10	339	
	32	4	538 404	538 409	538 406	538 407	538 410	538 402	10	330	
	32	5	538 504	538 509	538				10	350	
	63	3	568 304	568 306	568 309				5	661	
	63	4	568 404	568 409	568 406	568 407	568 410	568 402	5	720	
	63	5	568 504	568 509	568				5	779	

518 Panel sockets angled IP 67, flange screwed on