

LIITINALUSTAT F.I.A.M.E.


F.I.A.M.E. liitinalustat valmistetaan normien EN-60335 ja UL/CSA E255714 mukaan

 Materiaali: **BAKELITE®X65**

Paloluokka: UL94 V-0

Käyttölämpötila maks. +150 °C

Tyyppi	A	B	C	D	d	E	F	G	H	h	I	M
0116 MR	40	25	15	8,5	4,5	12...18	7,0	9	20	12	5	M4
0117 MR	50	32	18	9,5	5,5	15...21	6,0	9,5	22	12	6	M4
0118 MR	56	36	20	9,5	5,5	16...23	7,5	11,5	27	15	8	M5
0119 MR	70	45	25	10,5	6,5	23...28	9,5	13,0	31	16	9	M6
0120 MR	82	52	30	11,0	6,5	25...34	10,0	15,0	34	16	15	M6
0122 MR	95	60	35	16,0	7,5	29...39	12,0	19,0	47	23	14	M8
0125 MR	115	70	45	16,0	10,0	40...47	14,0	19,0	50	28	14	M10
0126 MR	125	80	45	16,0	11,0	40...49	15,0	21,0	58	32	15	M12
0128 MR	165	100	62	23,0	13,0	52...74	23,0	30,0	78	40	28	M16
0129 MR	240	150	90	30,0	17,0	84...95	22,0	35,0	105	56	32	M20

Liitinalustat toimitetaan liuskoineen (3kpl), aluslaattoineen (6kpl) sekä muttereineen (12kpl), irrallisina.

M	Maks Virta
M3	10 A
M4	16 A
M5	25 A
M6	63 A
M8	100 A
M10	160 A
M12	280 A
M14	280 A
M16	315 A
M20	400 A

