

DRAWN FLAT COPPER BAR



Oxygen-free electrolytically refined copper.

Quality SFS 2905 ISO Cu-OF-04

Electrical wire quality, good welding, excellent soldering.

Standard copper quality for electrical conductivity and the electrotechnical industry.

Usage: Wires, bus bars, coils, connectors, cables, commutators, induction devices, magnets, semiconductive components, waveguides etc.

Width mm	Thickness mm	Length m	Weight kg/m	Weight kg/pcs
15	3	4,0 - 4,2	0,40	1,60
20	3	4,0 - 4,2	0,54	2,16
20	5	4,0 - 4,2	0,89	3,56
20	10	4,0 - 4,2	1,78	7,12
25	3	4,0 - 4,2	0,67	2,68
25	4	4,0 - 4,2	0,90	3,60
25	5	4,0 - 4,2	1,12	4,48
25	6	4,0 - 4,2	1,34	5,36
30	5	4,0 - 4,2	1,34	5,36
30	10	4,0 - 4,2	2,68	10,72
40	5	4,0 - 4,2	1,78	7,12
40	6	4,0 - 4,2	2,15	8,60
40	8	4,0 - 4,2	2,86	11,44
40	10	4,0 - 4,2	3,57	14,28
50	5	4,0 - 4,2	2,23	8,92
50	8	4,0 - 4,2	3,58	14,32
50	10	4,0 - 4,2	4,46	17,84
60	6	4,0 - 4,2	3,21	12,84
60	8	4,0 - 4,2	4,29	17,16
60	10	4,0 - 4,2	5,35	21,40
80	8	4,0 - 4,2	5,72	22,88
80	10	4,0 - 4,2	7,14	28,56
100	10	4,0 - 4,2	8,93	35,72
120	10	4,0 - 4,2	10,70	42,80

The lengths and weights are nominal values.

Upon order it is also possible deliver the copper bars cut to measure.