

Model	Ø 2 mm	Ø 4 mm	Ø 6 mm	Ø 8 mm	Ø 10 mm	Ø 12 mm	Ø 14 mm	Ø 16 mm	Ø 18 mm	Ø 20 mm
KB 170	212	53	22	11	6	5	2			
KB 210	266	63	26	13	7	5	2			
KB 220	384	92	38	21	14	9	6	4	3	
KB 225	518	129	56	30	20	12	8	6	5	
GT 235	717	169	75	40	28	18	10	9	6	5
IT 240	841	210	83	46	31	20	12	10	6	4
IT 280	1028	244	108	54	39	27	16	10	10	13
HT 260	1072	259	111	58	40	27	17	11	10	10
IT 266	1158	284	126	68	45	31	20	14	14	9
SK 310	1323	321	133	75	51	30	27	18	12	10
GT 310	1323	321	133	75	51	30	27	18	12	12
HT 300K	1417	354	155	80	56	37	27	16	14	14
IT 300K	1464	354	155	80	56	37	27	16	14	15
HT 300	1555	379	159	91	58	36	24	21	14	14
IT 300	1617	404	173	93	59	43	29	21	14	14
HT 305	2126	526	236	122	85	57	40	26	22	21
HT 381	2566	623	268	146	97	61	52	34	23	20
HT 380	2740	685	288	159	109	68	54	37	27	27
SK 380	2749	667	288	153	109	65	52	26	23	20
GT 380	2749	667	288	153	109	65	52	38	33	23
IT 380	2827	693	309	161	110	69	55	38	27	27
SK 4821	3228	783	338	184	122	76	65	43	29	26
SK 450	3399	826	363	206	124	87	62	45	37	25
GT 450	3399	826	363	206	124	87	62	45	37	25
HT 482	3407	827	356	194	129	81	70	46	31	28
HT 385	4110	1017	438	244	164	106	82	61	43	39
HT 480	4110	1102	476	260	176	108	90	57	44	44
SK 302	4252	1063	472	245	170	118	81	52	46	42
HT 481	4532	1112	494	267	172	123	82	58	52	39
SK 4600	5742	1424	599	356	208	146	106	78	54	50
SK 4700	5742	1424	599	356	208	146	106	78	54	50
SK 4730	5742	1424	599	356	208	146	106	78	54	50
HT 485	6615	1638	724	397	264	168	135	93	69	63
HT 582	6928	1705	746	426	263	177	137	101	79	60



Model	Ø 2 mm	Ø 4 mm	Ø 6 mm	Ø 8 mm	Ø 10 mm	Ø 12 mm	Ø 14 mm	Ø 16 mm	Ø 18 mm	Ø 20 mm
SK 4601	8038	1998	847	493	292	211	156	109	79	70
SL 500 light	8421	2070	913	509	331	223	152	118	89	82
SK 4812	9064	2224	988	535	356	247	164	123	105	78
SK 4822	9064	2224	988	535	356	247	164	123	105	78
SL 500	9393	2293	1019	573	369	254	169	133	101	74
SK 4731	9646	2411	1023	597	350	255	187	135	96	87
SK 4823	9722	2351	1014	553	384	230	197	136	92	82
SK 4701	10335	2572	1096	643	375	270	200	146	104	91
SK 4602	11484	2871	1213	712	417	299	219	161	112	104
SK 460	11823	2898	1302	689	463	306	225	169	126	115
SK 4813	13596	3337	1483	803	539	370	247	182	164	122
SK 580	18115	4437	2012	1073	690	472	368	250	223	168

Other cable lengths at www.schill.de/en





IT 300K.OPEN



- open design for self-tooling
- spool and core made of plastic
- powder-coated steel carrying handle
- with locking brake screw
- without cable
- drum-ø 300 mm

Order No.	Item	Version	Weight (kg)
260 00 000 000	IT 300K.OPEN	open	2.22

IT 380.OPEN



- open design for self-tooling
- spool and core made of plastic
- powder-coated steel carrying handle
- with locking brake screw
- without cable
- drum-ø 380 mm

Order No.	item	Version	Weight (kg)
290 00 000 000	IT 380.OPEN	open	3.45



GT 235.OPEN



- open design for self-tooling with locking brake screw
- without cable
- drum-ø 235 mm

Order No.	Item	Version	Weight (kg)
200 00 000 000	GT 235.OPEN	open	0.95

GT 310.OPEN



- open design for self-tooling
- with locking brake screw
- without cable
- drum-ø 310 mm

Order No.	item	Version	Weight (kg)
270 00 000 000	GT 310.OPEN	open	1.61



GT 380.OPEN



- open design for self-tooling with locking brake screw
- without cable
- travelling unit available as accessory
- drum-ø 380 mm

Order No.	Item	Version	Weight (kg)
275 00 000 000	GT 380.OPEN	open	3.90

GT 450.OPEN



- open design for self-tooling with locking brake screw
- without cable
- travelling unit available as accessory
- drum-ø 450 mm

Order No.	Item	Version	Weight (kg)
280 00 000 000	GT 450.OPEN	open	5.14



HT 300K.OPEN



- open design for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 141 mm

Order No.	Item	Version	Weight (kg)
332 00 000 000	HT 300K.OPEN	open	2.95

HT 305.OPEN



- open design for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 209 mm

Order No. Item	Version	Weight (kg)
338 00 000 000 HT 305.OPEN	open	3.99



HT 380.OPEN



- open design for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- travelling column unit available as accessory
- core-ø 178 mm

Order No.	Item	Version	Weight (kg)
363 00 000 000	HT 380.OPEN	open	5.14

HT 381.OPEN



- open design for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- travelling column unit available as accessory
- core-ø 240 mm

Order No.	Item	Version	Weight (kg)
364 00 000 000	HT 381.OPEN	open	5.63



HT 385.OPEN



- open design for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- · travelling column unit available as accessory
- core width 210 mm

Order No.	Item	Version		Weight (kg)
368 00 000 000	HT 385.OPEN	open		5.50
368 00 000 500	HT 385.OPEN	open	core opening 60x60 mm	5.40

HT 480.OPEN



- open design for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- travelling column unit available as accessory
- core width 141 mm

Order No.	Item	Version	Weight (kg)
376 00 000 000	HT 480.OPEN	open	7.16



HT 481.OPEN



- open design for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- travelling column unit available as accessory
- core-ø 240 mm

Order No.	Item	Version	Weight (kg)
374 00 000 000	HT 481.OPEN	open	7.72

HT 482.OPEN



- open design for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- travelling column unit available as accessory
- core-ø 320 mm

Order No.	Item	Version	Weight (kg)
375 00 000 000	HT 482.OPEN	open	8.12



HT 485.OPEN



- open design for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- travelling column unit available as accessory
- drum-ø 460 mm

Order No.	Item	Version		Weight (kg)
376 00 001 000	HT 485.OPEN	open		7.47
376 00 000 500	HT 485.OPEN	open	core opening 60x60 mm	7.19

HT 582.OPEN



- open design for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- travelling column unit available as accessory
- drum-ø 580 mm

Order No.	item	Version	Weight (kg)
380 00 000 000	HT 582.OPEN	open	14.32



SK 310.OPEN



- professional stage cable drum
- open design for self-tooling
- spool made of special rubber
- powder-coated steel frame
- with locking brake screw
- without cable
- stackable with SK 310
- transport trolley available as accessory
- drum-ø 310 mm

Order No.	Item	Version	Weight (kg)
402 00 000 000	SK 310.OPEN	open	4.41

SK 380.OPEN



- professional stage cable drum
- open design for self-tooling
- · spool made of special rubber
- powder-coated steel frame
- with locking brake screw
- without cable
- stackable with SK 380
- transport trolley available as accessory
- drum-ø 380 mm

Order No.	Item	Version	Weight (kg)
403 00 000 000	SK 380.OPEN	open	5.93



SK 450.OPEN



- professional stage cable drum
- open design for self-tooling
- spool made of special rubber
- powder-coated steel frame
- with locking brake screw
- without cable
- stackable with SK 450
- transport trolley available as accessory
- drum-ø 450 mm

Order No.	Item	Version	Weight (kg)
404 00 000 000	SK 450.OPEN	open	7.24



SK 302.OPEN



- professional stage cable drum for longer cable lengths
- open design for self-tooling
- powder-coated sheet steel discs
- powder-coated steel frame
- core made of plastic
- · with locking brake screw
- without cable
- stackable with SK 302
- drum-ø 300 mm

Order No.	Item	Version	Weight (kg)
405 00 000 000	SK 302.OPEN	open	10.00

FSK 485.OPEN



- professional stage cable drum for longer cable lengths
- open version for self-tooling
- powder-coated sheet steel discs
- powder-coated sheet steel dis
- core made of plastic
- with locking brake screw
- without cable
- stackable with FSK 485
- mobile with 2 wheels

Order No.	Item	Version	Weight (kg)
407 00 000 000	FSK 485.OPEN	open	7.24



IT 240.S0



- with closed front panel
- discs made of plastic
- with small core made of plastic
- powder-coated steel carrying handle
- with locking brake screw
- without cable
- drum-ø 240 mm

Order No.	Item	Version	Weight (kg)
210 01 000 000	IT 240.50	with closed front panel	1.61

IT 300.S0



- with closed front panel
- with locking brake screw
- with small core
- without cable
- drum-ø 300 mm

Order No.	Item	Version	Weight (kg)
250 01 000 000	IT 300.S0	with closed front panel	1.70



HT 260.S0



- with closed front panel
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- drum-ø 260 mm

Order No.	Item	Version	Weight (kg)
315 01 000 000	HT 260.S0	with closed front panel	2.27

HT 300.S0



- with closed front panel
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- drum-ø 300 mm

Order No.	Item	Version	Weight (kg)
335 01 000 000	HT 300.S0	with closed front panel	2.73



SK 4600.S0



- professional stage cable drum for longer cable lengths
- · with closed front panel
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- with truss core
- with crank handle
- with locking brake screw
- without cable
- not stackable
- transport trolley available as accessory
- core width 250 mm

Order No.	Item	Version	Weight (kg)
413 01 000 000	SK 4600.S0	with closed front panel	14.00

SK 4601.S0



- professional stage cable drum for longer cable lengths
- with closed front panel
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- with truss core
- with crank handle
- with locking brake screw
- without cable
- not stackable
- transport trolley available as accessory
- core width 320 mm

Order No.	item	Version	Weight (kg)
414 01 000 000	SK 4601.S0	with closed front panel	14.93



SK 4602.S0



- professional stage cable drum for longer cable lengths
- · with closed front panel
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- with truss core
- · with crank handle
- with locking brake screw
- without cable
- not stackable
- transport trolley available as accessory
- core width 500 mm

Order No.	Item	Version	Weight (kg)
415 01 000 000	SK 4602.S0	with closed front panel	16.79

SK 4700.S0



- professional stage cable drum for longer cable lengths
- with closed front panel
- powder-coated sheet steel discs
- powder-coated steel frame
- with truss core
- with crank handle
- with locking brake screw
- without cable
- stackable with SK 4700 / SK 4730 / SK 4812 / SK 4822
- transport trolley available as accessory
- core width 250 mm

Order No.	Item	Version	Weight (kg)
420 01 000 000	SK 4700.S0	with closed front panel	19.50



SK 4701.S0



- professional stage cable drum for longer cable lengths
- with closed front panel
- powder-coated sheet steel discs
- powder-coated steel frame
- with truss core
- with crank handle
- with locking brake screw
- · without cable
- stackable with SK 4701 / SK 4731 / SK 4813 / SK 4823
- transport trolley available as accessory
- core width 450 mm

Order No.	Item	Version	Weight (kg)
421 01 000 000	SK 4701.S0	with closed front panel	21.50

SK 4730.S0



- professional stage cable drum for longer cable lengths
- with closed front panel
- with additional intermediate plate
- powder-coated sheet steel discs
- powder-coated steel frame
- with truss core
- with crank handle
- with locking brake screw
- without cable
- stackable with SK 4730 / SK 4700 / SK 4812 / SK 4822
- transport trolley available as accessory
- core width 250 mm

Order No.	Item	Version	Weight (kg)
425 01 000 000	SK 4730.50	with closed front panel	21.00



SK 4731.S0



- professional stage cable drum for longer cable lengths
- with closed front panel
- with additional intermediate plate
- powder-coated sheet steel discs
- powder-coated steel frame
- with truss core
- with crank handle
- with locking brake screw
- without cable
- stackable with SK 4731 / SK 4701 / SK 4813 / SK 4823
- transport trolley available as accessory
- core width 420 mm

Order No.	Item	Version	Weight (kg)
426 01 000 000	SK 4731.S0	with closed front panel	23.57

SK 460.250.460 Alu



- professional stage cable drum for particularly long cable lengths
- with closed front panel
- powder-coated sheet steel discs, color stone-grey
- coat ring made of polycarbonate
- black frame made of aluminium
- with crank handle
- with spring-loaded brake
- stackable with SK 460
- drum-ø 460 mm

Order No.	Item	Version	Weight (kg)
434 02 000 000	SK 460.250.460-Alu	with closed front panel	19.00



SK 580.320.450 Alu



- professional stage cable drum for particularly long cable lengths
- with closed front panel
- powder-coated sheet steel discs, color stone-grey
- coat ring made of polycarbonate
- black frame made of aluminium
- with crank handle
- with spring-loaded brake
- stackable with SK 580
- drum-ø 580 mm

Order No.	Item	Version	Weight (kg)
444 02 000 000	SK 580.320.450-Alu	with closed front panel	23.50

SK 580.320.450



- professional stage cable drum for particularly long cable lengths
- with closed front panel
- powder-coated sheet steel discs, color stone-grey
- coat ring made of polycarbonate
- black frame made of sheet steel
- with crank handle
- with spring-loaded brake
- stackable with SK 580
- drum-ø 580 mm

Order No.	item	Version	Weight (kg)
444 01 000 000	SK 580.320.450	with closed front panel	43.00



KB 210.S0



- with blank cover for self-tooling
- without cable
- casing-ø 175 mm

Order No.	Item	Version	Weight (kg)
140 01 000 000	KB 210.S0	with blank cover	0.40

KB 225.S0



- with blank cover for self-tooling
- without cable
- casing-ø 222 mm

Order No.	Item	Version	Weight (kg)
170 01 000 000	KB 225.S0	with blank cover	0.70



KB 170.S0



- especially free-moving configuration with blank cover for self-tooling
- without cable
- casing width 181 mm

Order No.	Item	Version	Weight (kg)
120 01 000 000	KB 170.S0	with blank cover	0.60

KB 220.S0



- especially free-moving configuration with blank cover for self-tooling
- without cable
- casing width 220 mm

Order No.	Item	Version	Weight (kg)
150 01 000 000 I	KB 220.S0	with blank cover	0.76



IT 266.S0



- with blank cover for self-tooling with locking brake screw
- without cable
- drum-ø 266 mm

Order No.	Item	Version	Weight (kg)
230 01 000 000	IT 266.S0	with blank cover	1.25

IT 280.S0



- with blank cover for self-tooling spool made of plastic
- steel carrying handle
- with locking brake screw
- without cable
- drum-ø 280 mm

Order No.	Item	Version	Weight (kg)
240 01 000 000	IT 280.S0	with blank cover	1.37



IT 300K.S0



- with blank cover for self-tooling
- discs and core made of plastic
- powder-coated steel carrying handle
- with locking brake screw
- without cable
- drum-ø 300 mm

Order No.	Item	Version	Weight (kg)
260 01 000 000	IT 300K.S0	with blank cover	2.37

IT 380.S0



- with blank cover for self-tooling
- discs and core made of plastic
- powder-coated steel carrying handle
- with locking brake screw
- for larger cable diameters and lengths
- without cable
- drum-ø 380 mm

Order No.	item	Version	Weight (kg)
290 01 000 000	IT 380.S0	with blank cover	3.65



GT 235.S0



- with blank cover for self-tooling with locking brake screw
- without cable
- drum-ø 235 mm

Order No.	Item	Version	Weight (kg)
200 01 000 000	GT 235.S0	with blank cover	1.02

GT 310.S0



- with blank cover for self-tooling
- with locking brake screw
- without cable
- drum-ø 310 mm

Order No.	item	Version	Weight (kg)
270 01 000 000	GT 310.S0	with blank cover	1.76



GT 380.S0



- with blank cover for self-tooling with locking brake screw
- without cable
- travelling unit available as accessory
- drum-ø 380 mm

Order No.	Item	Version	Weight (kg)
275 01 000 000	GT 380.S0	with blank cover	4.15

GT 450.S0



- with blank cover for self-tooling
- with locking brake screw
- without cable
- travelling unit available as accessory
- drum-ø 450 mm

Order No.	item	Version	Weight (kg)
280 01 000 000	GT 450.S0	with blank cover	5.20



HT 300K.S0



- with blank cover for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 141 mm

Order No.	Item	Version	Weight (kg)
336 01 000 000	HT 300K.S0	with blank cover	3.10

HT 305.S0



- with blank cover for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 209 mm

Order No.	Item	Version	Weight (kg)
338 01 000 000	HT 305.S0	with blank cover	4.14



HT 380.S0



- with blank cover for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- travelling column unit available as accessory
- core-ø 178 mm

Order No.	Item	Version	Weight (kg)
365 01 000 000	HT 380.S0	with blank cover	5.28

HT 381.S0



- with blank cover for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- travelling column unit available as accessory
- core-ø 240 mm

Order No.	Item	Version	Weight (kg)
364 01 000 000	HT 381.S0	with blank cover	5.78



HT 385.S0



- with blank cover for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- travelling column unit available as accessory
- core-ø 176 mm

Order No.	Item	Version	Weight (kg)
368 01 000 000	HT 385.S0	with blank cover	5.65

HT 480.S0



- with blank cover for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- travelling column unit available as accessory
- core-ø 178 mm

Order No.	Item	Version		Weight (kg)
374 01 000 000	HT 480.S0	with blank cover		7.31
374 01 000 500	HT 480.S0	with blank cover	sloping cable entry point	7.34



HT 481.S0



- with blank cover for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- travelling column unit available as accessory
- core-ø 240 mm

Order No.	Item	Version	Weight (kg)
377 01 000 000	HT 481.S0	with blank cover	8.73

HT 482.S0



- with blank cover for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- travelling column unit available as accessory
- core-ø 320 mm

Order No.	Item	Version	Weight (kg)
378 01 000 000	HT 482.S0	with blank cover	8.27



HT 485.S0



- with blank cover for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- travelling column unit available as accessory
- core-ø 176 mm

Order No.	Item	Version	Weight (kg)
376 01 001 000	HT 485.S0	with blank cover	7.62

HT 582.S0



- with blank cover for self-tooling
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- travelling column unit available as accessory
- core-ø 320 mm

Order No.	Item	Version	Weight (kg)
375 01 000 000	HT 582.S0	with blank cover	12.98



SK 310.S0



- professional stage cable drum
- with blank cover for self-tooling
- spool made of special rubber
- powder-coated steel frame
- with locking brake screw
- without cable
- stackable with SK 310
- transport trolley available as accessory
- drum-ø 310 mm

Order No.	Item	Version	Weight (kg)
402 01 000 000	SK 310.S0	with blank cover	6.03

SK 380.S0



- professional stage cable drum
- with blank cover for self-tooling
- spool made of special rubber
- powder-coated steel frame
- with locking brake screw
- without cable
- stackable with SK 380
- transport trolley available as accessory
- drum-ø 380 mm

Order No.	Item	Version	Weight (kg)
403 01 000 000	SK 380.S0	with blank cover	6.03



SK 450.S0



- professional stage cable drum
- with blank cover for self-tooling
- spool made of special rubber
- powder-coated steel frame
- with locking brake screw
- without cable
- stackable with SK 450
- transport trolley available as accessory
- drum-ø 450 mm

Order No.	Item	Version	Weight (kg)
404 01 000 000	SK 450.S0	with blank cover	6.03



SK 302.S0



- professional stage cable drum for longer cable lengths
- with blank cover for self-tooling
- powder-coated sheet steel discs
- powder-coated steel frame
- core made of plastic
- with locking brake screw
- without cable
- stackable with SK 302
- core width 419 mm

Order No.	Item	Version	Weight (kg)
405 01 000 000	SK 302.S0	with blank cover	10.60

SK 4821.S0



- professional stage cable drum for longer cable lengths
- with blank cover for self-tooling
- powder-coated sheet steel discs
- powder-coated steel frame
- core made of plastic
- with locking brake screw
- without cable
- stackable with SK 4821
- transport trolley available as accessory
- core width 169 mm

Order No.	Item	Version	Weight (kg)
431 01 000 000	SK 4821.S0	with blank cover	13.40



SK 4822.S0



- professional stage cable drum for longer cable lengths
- with blank cover for self-tooling
- powder-coated sheet steel discs
- powder-coated steel frame
- core made of plastic
- with locking brake screw
- without cable
- stackable with SK 4822 / SK 4700 / SK 4730 / SK 4812
- transport trolley available as accessory
- core width 338 mm

Order No.	Item	Version	Weight (kg)
435 01 000 000	SK 4822.S0	with blank cover	19.90

SK 4823.S0



- professional stage cable drum for longer cable lengths
- with blank cover for self-tooling
- powder-coated sheet steel discs
- powder-coated steel frame
- core made of plastic
- with locking brake screw
- without cable
- stackable with SK 4823 / SK 4701 / SK 4731 / SK 4813
- transport trolley available as accessory
- core width 504 mm

Order No.	item	Version	Weight (kg)
436 01 000 000	SK 4823.S0	with blank cover	22.00



IT 266.RM



- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- without cable
- drum-ø 266 mm

Order No.	Item	Version	Weight (kg)
230 39 000 000	IT 266.RM	with RM-auxiliary spool	1.26

IT 300K.RM



- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- discs and core made of plastic
- powder-coated steel carrying handle
- without cable
- drum-ø 300 mm

Order No.	tem	Version		Weight (kg)
260 39 000 000 IT	T 300K.RM	with RM-auxiliary spool	with velcro strap	2.38



IT 380.RM



- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- for larger cable diameters and lengths
- discs and core made of plastic
- powder-coated steel carrying handle
- without cable
- drum-ø 380 mm

Order No.	Item	Version		Weight (kg)
290 39 000 000	IT 380.RM	with RM-auxiliary spool	with velcro strap	3.61



SL 500 light



- special cable drum with frame made of powder-coated steel tube, color black
- discs and coat-ring made of glass-fibre reinforced polycarbonate, color stone-grey
- with 6 RM-angle made of plastic
- with brake
- with crank handle
- stackable with SL 500 light / SL 500

Order No.	Item	Version	Weight (kg)
440 00 000 001	SL 500 light	with RM-auxiliary angle	18.00



GT 235.RM



- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- without cable
- drum-ø 235 mm

Order No.	Item	Version		Weight (kg)
200 39 000 000	GT 235.RM	with RM-auxiliary spool	core opening ø 43 mm	1.03

GT 310.RM



- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- without cable
- drum-ø 310 mm

Order No.	Item	Version		Weight (kg)
270 39 000 000	GT 310.RM	with RM-auxiliary spool	with velcro strap, core opening ø 43 mm	1.78
270 39 000 700	GT 310.RM	with RM-auxiliary spool	with leather strap, core opening ø 43 mm	1.78



GT 380.RM



- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- without cable
- travelling unit available as accessory
- drum-ø 380 mm

Order No.	Item	Version		Weight (kg)
275 39 000 000	GT 380.RM	with RM-auxiliary spool	with velcro strap, core opening ø 50 mm	4.25
275 39 000 700	GT 380.RM	with RM-auxiliary spool	with leather strap, core opening ø 50 mm	4.25

GT 450.RM



- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- without cable
- travelling unit available as accessory
- drum-ø 450 mm

Order No.	Item	Version		Weight (kg)
280 39 000 000	GT 450.RM	with RM-auxiliary spool	with velcro strap, core opening ø 60 mm	5.58



HT 300K.RM



- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- · powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- without cable
- core width 141 mm

Order No.	Item	Version		Weight (kg)
336 39 000 000	HT 300K.RM	with RM-auxiliary spool	with velcro strap	3.12
336 39 000 500	HT 300K.RM	with RM-auxiliary spool	velcro strap, sloping cable entry point	3.12

HT 305.RM



- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- without cable
- core width 210 mm

Order No.	item	Version		Weight (kg)
338 39 000 000	HT 305.RM	with RM-auxiliary spool	with velcro strap	4.15
338 39 000 500	HT 305.RM	with RM-auxiliary spool	velcro strap, sloping cable entry point	3.92
338 39 000 500	HT 305.RM	with RM-auxiliary spool	velcro strap, sloping cable entry point	3.9



HT 380.RM



- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- · powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- without cable
- travelling column unit available as accessory
- core-ø 178 mm

Order No.	Item	Version		Weight (kg)
365 39 000 000	HT 380.RM	with RM-auxiliary spool	with velcro strap	5.30
365 39 000 500	HT 380.RM	with RM-auxiliary spool	velcro strap, sloping cable entry point	5.30
365 39 000 501	HT 380.RM	with RM-auxiliary spool	velcro strap, core opening 43x43 mm	5.30

HT 381.RM



- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- without cable
- travelling column unit available as accessory
- core-ø 240 mm

Order No. Item	Version		Weight (kg)
364 39 000 000 HT 381.RM	with RM-auxiliary spool	with velcro strap	5.79



HT 385.RM



- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- · powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- without cable
- travelling column unit available as accessory
- core-ø 176 mm

Order No.	Item	Version		Weight (kg)
368 39 000 000	HT 385.RM	with RM-auxiliary spool	with velcro strap	5.66
368 39 000 500	HT 385.RM	with RM-auxiliary spool	with velcro strap, core opening 60x60 mm	5.66

HT 480.RM



- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- without cable
- travelling column unit available as accessory
- core-ø 178 mm

Order No.	Item	Version		Weight (kg)
374 39 000 000	HT 480.RM	with RM-auxiliary spool	with velcro strap	7.30
374 39 000 500	HT 480.RM	with RM-auxiliary spool	velcro strap, sloping cable entry point	6.55



HT 481.RM



- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- without cable
- travelling column unit available as accessory
- core-ø 240 mm

Order No.	Item	Version		Weight (kg)
377 39 000 000	HT 481.RM	with RM-auxiliary spool	with velcro strap	8.73

HT 482.RM



- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- without cable
- travelling column unit available as accessory
- core-ø 320 mm

Order No.	Item	Version		Weight (kg)
378 39 000 000	HT 482.RM	with RM-auxiliary spool	with velcro strap	8.28



HT 485.RM



- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- without cable
- travelling column unit available as accessory
- core-ø 176 mm

Order No.	Item	Version		Weight (kg)
376 39 001 000	HT 485.RM	with RM-auxiliary spool	with velcro strap	7.63
376 39 001 500	HT 485.RM	with RM-auxiliary spool	velcro strap, core opening 60x60 mm	6.43

HT 582.RM



- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- without cable
- travelling column unit available as accessory
- core-ø 320 mm

Order No.	Item	Version		Weight (kg)
375 39 000 000	HT 582.RM	with RM-auxiliary spool	with velcro strap	12.39



SK 310.RM



- professional stage cable drum
- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- · with locking brake screw
- spool made of special rubber
- powder-coated steel frame
- stackable with SK 310
- without cable
- transport trolley available as accessory
- drum-ø 310 mm

Order No.	Item	Version		Weight (kg)
402 39 000 000	SK 310.RM	with RM-auxiliary spool	velcro strap, core opening ø 43 mm	6.20

SK 380.RM



- professional stage cable drum
- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- spool made of special rubber
- powder-coated steel frame
- stackable with SK 380
- without cable
- transport trolley available as accessory
- drum-ø 380 mm

Order No.	Item	Version		Weight (kg)
403 39 000 000	SK 380.RM	with RM- auxiliary spool	velcro strap, core opening ø 50 mm	6.23



SK 450.RM



- professional stage cable drum
- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- spool made of special rubber
- powder-coated steel frame
- stackable with SK 450
- without cable
- transport trolley available as accessory
- drum-ø 450 mm

Order No.	Item	Version		Weight (kg)
404 39 000 000	SK 450.RM	with RM-auxiliary spool	velcro strap, core opening ø 60 mm	6.14



SK 302.RM



- professional stage cable drum for longer cable lengths
- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- powder-coated sheet steel discs
- · powder-coated steel frame
- core made of plastic
- stackable with SK 302
- without cable
- core width 419 mm

Order No.	Item	Version		Weight (kg)
405 39 000 000	SK 302.RM	with RM-auxiliary spool	with velcro strap	10.41

SK 4600.RM



- professional stage cable drum for longer cable lengths
- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- powder-coated sheet steel discs
- powder-coated steel handle
- with truss core
- with crank handle
- not stackable
- without cable
- transport trolley available as accessory
- core width 250 mm

Order No.	Item	Version		Weight (kg)
413 39 000 000	SK 4600.RM	with RM-auxiliary spool	with velcro strap	13.40



SK 4601.RM



- professional stage cable drum for longer cable lengths
- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- · with locking brake screw
- powder-coated sheet steel discs
- powder-coated steel handle
- with truss core
- with crank handle
- not stackable
- without cable
- · transport trolley available as accessory
- core width 350 mm

Order No.	Item	Version		Weight (kg)
414 39 000 000	SK 4601.RM	with RM-auxiliary spool	with velcro strap	15.13

SK 4602.RM



- professional stage cable drum for longer cable lengths
- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- powder-coated sheet steel discs
- powder-coated steel handle
- with truss core
- with crank handle
- not stackable
- without cable
- transport trolley available as accessory
- core width 500 mm

Order No.	Item	Version		Weight (kg)
415 39 000 000	SK 4602.RM	with RM-auxiliary spool	with velcro strap	16.99



SK 4700.RM



- professional stage cable drum for longer cable lengths
- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- powder-coated sheet steel discs
- powder-coated steel frame
- with truss core
- with crank handle
- stackable with SK 4700 / SK 4730 / SK 4812 / SK 4822
- without cable
- transport trolley available as accessory
- core width 250 mm

Order No.	Item	Version		Weight (kg)
420 39 000 000	SK 4700.RM	with RM-auxiliary spool	with velcro strap	18.78

SK 4701.RM



- professional stage cable drum for longer cable lengths
- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- powder-coated sheet steel discs
- powder-coated steel frame
- with truss core
- with crank handle
- stackable with SK 4701 / SK 4731 / SK 4813 / SK 4823
- without cable
- transport trolley available as accessory
- core width 450 mm

Order No.	Item	Version		Weight (kg)
421 39 000 000	SK 4701.RM	with RM-auxiliary spool	with velcro strap	19.40



SK 4812.RM



- professional stage cable drum for longer cable lengths
- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- powder-coated sheet steel discs
- powder-coated steel frame
- core made of plastic
- with 1 axle bearing
- with 1 outside storage
- with folding crank
- stackable with SK 4812 / SK 4700 / SK 4730 / SK 4822
- without cable
- · transport trolley available as accessory
- core width 336 mm

Order No.	Item	Version		Weight (kg)
434 39 000 000	SK 4812.RM	with RM-auxiliary spool	with velcro strap, core opening 60x60 mm	17.90

SK 4813.RM



- professional stage cable drum for longer cable lengths
- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- powder-coated sheet steel discs
- powder-coated steel frame
- core made of plastic
- with 1 axle bearing
- with 1 outside storage
- with folding crank
- stackable with SK 4813 / SK 4701/ SK 4731 / SK 4823
- without cable
- transport trolley available as accessory
- core width 504 mm

Order No.	Item	Version		Weight (kg)
438 39 000 000	SK 4813.RM	with RM-auxiliary spool	with velcro strap, core opening 60x60 mm	17.90



SK 4822.RM



- professional stage cable drum for longer cable lengths
- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- powder-coated sheet steel discs
- powder-coated steel frame
- core made of plastic
- stackable with SK 4822 / SK 4812 / SK 4700 / SK 4730
- without cable
- transport trolley available as accessory
- core width 338 mm

Order No.	Item	Version		Weight (kg)
435 39 000 000	SK 4822.RM	with RM-auxiliary spool	with velcro strap	17.90

SK 4823.RM



- professional stage cable drum for longer cable lengths
- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with RM-auxiliary spool
- with locking brake screw
- powder-coated sheet steel discs
- powder-coated steel frame
- core made of plastic
- stackable with SK 4823 / SK 4701 / SK 4731 / SK 4813
- without cable
- transport trolley available as accessory
- core width 504 mm

Order No.	Item	Version		Weight (kg)
436 39 000 000	SK 4823.RM	with RM-auxiliary spool	with velcro strap	19.90



SL 500



The SL 500 has been specially developed to suit the wishes and requirements of users, in particular in the broadcasting sector. This model is suited to robust, professional use and has 4 strengthened reel holders.

In addition it is equipped as standard with the reputable MFK cover, so that the connections are protected in the cover for safety and ease of access. The adjustable brakes prevent unintentional rolling away.

- MFK cover with latching door
- powder-coated steel tube frame, color black
- discs and coat ring made of glass-fibre reinforced polycarbonate, color stone-grey
- strengthened reel holders
- solid crank handle
- fold-away carrying handle
- special brakes
- stackable with SL 500 / SL 500 light
- stackable up to 12 pcs. fit onto a EURO palette
- · without cable

Order No.	Item	Version	Weight (kg)
440 00 000 000	SL 500	with latching door (2 hinges)	18.00



GT 310.MFK



- with latching door
- the door ensures optimal protection of your high quality cable connectors; the door allows you to store cable connectors inside drum to prevent damage to your valuable connectors during rolling up and off the cable drum
- with locking brake screw
- without cable
- drum-ø 310 mm

Order No.	Item	Version		Weight (kg)
270 01 000 540	GT 310.MFK	with latching door (1 hinge)	core opening ø 43 mm	1.78

GT 380.MFK



- with latching door
- the door ensures optimal protection of your high quality cable connectors; the door allows you to store cable connectors inside drum to prevent damage to your valuable connectors during rolling up and off the cable drum
- with locking brake screw
- without cable
- travelling unit available as accessory
- drum-ø 380 mm

Order No.	Item	Version		Weight (kg)
275 01 000 550	GT 380.MFK	with latching door (2 hinges)	core opening ø 50 mm	4.22





GT 450.MFK



- with latching door
- the door ensures optimal protection of your high quality cable connectors; the door allows you to store cable connectors inside drum to prevent damage to your valuable connectors during rolling up and off the cable drum
- with locking brake screw
- without cable
- travelling unit available as accessory
- drum-ø 450 mm

Order No.	Item	Version		Weight (kg)
280 00 000 560	GT 450.MFK	with latching door (2 hinges)	core opening ø 60 mm	5.60



HT 300K.MFK



- with latching door
- the door ensures optimal protection of your high quality cable connectors;
 the door allows you to store cable connectors inside drum to prevent damage to your valuable connectors during rolling up and off the cable drum
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- · with locking brake screw
- without cable
- core width 141 mm

Order No.	Item	Version		Weight (kg)
332 30 000 000	HT 300K.MFK	with latching door (1 hinge)	core opening 43x43 mm	2.95

HT 305.MFK



- · with latching door
- the door ensures optimal protection of your high quality cable connectors;
 the door allows you to store cable connectors inside drum to prevent damage to your valuable connectors during rolling up and off the cable drum
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 209 mm

Order No.	Item	Version		Weight (kg)
338 30 000 000	HT 305.MFK	with latching door (1 hinge)	core opening 60x60 mm	3.99



HT 380.MFK



- · with latching door
- the door ensures optimal protection of your high quality cable connectors;
 the door allows you to store cable connectors inside drum to prevent damage to your valuable connectors during rolling up and off the cable drum
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- travelling column unit available as accessory
- core width 141 mm

Order No.	Item	Version		Weight (kg)
365 30 000 000	HT 380.MFK	with latching door (1 hinge)	core opening 43x43 mm	5.14

HT 385.MFK



- · with latching door
- the door ensures optimal protection of your high quality cable connectors;
 the door allows you to store cable connectors inside drum to prevent damage to your valuable connectors during rolling up and off the cable drum
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- · with locking brake screw
- without cable
- travelling column unit available as accessory
- core width 209 mm

Order No.	Item	Version		Weight (kg)
368 01 000 501	HT 385.MFK	with latching door (1 hinge)	core opening 60x60 mm	5.65



HT 480.MFK



- · with latching door
- the door ensures optimal protection of your high quality cable connectors;
 the door allows you to store cable connectors inside drum to prevent damage to your valuable connectors during rolling up and off the cable drum
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- · with locking brake screw
- without cable
- · travelling column unit available as accessory
- core width 141 mm

Order No.	Item	Version		Weight (kg)
376 30 000 000	HT 480.MFK	with latching door (1 hinge)	core opening 43x43 mm	7.16

HT 485.MFK



- · with latching door
- the door ensures optimal protection of your high quality cable connectors;
 the door allows you to store cable connectors inside drum to prevent damage to your valuable connectors during rolling up and off the cable drum
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- travelling column unit available as accessory
- core width 209 mm

Order No. Item	Version		Weight (kg)
376 00 000 560 HT 485.MFK	with latching door (1 hinge)	core opening 60x60 mm	7.19



HT 582.MFK



- · with latching door
- the door ensures optimal protection of your high quality cable connectors;
 the door allows you to store cable connectors inside drum to prevent damage to your valuable connectors during rolling up and off the cable drum
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- · travelling column unit available as accessory
- core width 169 mm

Order No.	Item	Version		Weight (kg)
375 30 000 000	HT 582.MFK	with latching door (1 hinge)	core opening 60x60 mm	7.16



SK 310.MFK



- professional stage cable drum
- · with latching door
- the door ensures optimal protection of your high quality cable connectors;
 the door allows you to store cable connectors inside drum to prevent damage to your valuable connectors during rolling up and off the cable drum
- spool made of special rubber
- powder-coated steel frame
- with locking brake screw
- stackable with SK 310
- without cable
- transport trolley available as accessory
- drum-ø 310 mm

Order No.	Item	Version		Weight (kg)
402 70 000 000	SK 310.MFK	with latching door (1 hinge)	core opening ø 43 mm	6.20

SK 380.MFK



- professional stage cable drum
- with latching door
- the door ensures optimal protection of your high quality cable connectors; the door allows you to store cable connectors inside drum to prevent damage to your valuable connectors during rolling up and off the cable drum
- spool made of special rubber
- powder-coated steel frame
- with locking brake screw
- stackable with SK 380
- without cable
- transport trolley available as accessory
- drum-ø 380 mm

Order No.	Item	Version		Weight (kg)
403 00 000 550	SK 380.MFK	with latching door (2 hinges)	core opening ø 50 mm	6.03



SK 450.MFK



- professional stage cable drum
- with latching door
- the door ensures optimal protection of your high quality cable connectors;
 the door allows you to store cable connectors inside drum to prevent damage to your valuable connectors during rolling up and off the cable drum
- spool made of special rubber
- powder-coated steel frame
- with locking brake screw
- stackable with SK 450
- without cable
- transport trolley available as accessory
- drum-ø 450 mm

Order No.	Item	Version		Weight (kg)
404 00 000 560	SK 450.MFK	with latching door (2 hinges)	core opening ø 60 mm	7.64



SK 302.MFK



- professional stage cable drum for longer cable lengths
- with latching door
- the door ensures optimal protection of your high quality cable connectors;
 the door allows you to store cable connectors inside drum to prevent damage to your valuable connectors during rolling up and off the cable drum
- powder-coated sheet steel discs
- powder-coated steel frame
- core made of plastic
- with locking brake screw
- stackable with SK 302
- without cable
- core width 419 mm

Order No.	Item	Version	Weight (kg)
405 70 000 000	SK 302.MFK	with latching door (1 hinge)	10.41



GT 380.RMFK



- with latching door and RM-auxiliary spool with velcro strap
- the door ensures optimal protection of your high quality cable connectors;
 the door allows you to store cable connectors inside drum to prevent damage to your valuable connectors during rolling up and off the cable drum
- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- · with locking brake screw
- · without cable
- · travelling unit available as accessory
- drum-ø 380 mm

Order No.	Item	Version		Weight (kg)
275 29 000 000	GT 380.RMFK	with latching door (2 hinges)	RM spool, flange hole ø 51 mm	4.22

GT 450.RMFK



- with latching door and RM-auxiliary spool with velcro strap
- the door ensures optimal protection of your high quality cable connectors;
 the door allows you to store cable connectors inside drum to prevent damage to your valuable connectors during rolling up and off the cable drum
- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with locking brake screw
- without cable
- travelling unit available as accessory
- drum-ø 450 mm

Order No.	Item	Version		Weight (kg)
280 29 000 000	GT 450.RMFK	with latching door (2 hinges)	RM-spool, flange hole ø 51 mm	5.60



SK 380.RMFK



- professional stage cable drum
- · with latching door and RM-auxiliary spool with velcro strap
- the door ensures optimal protection of your high quality cable connectors;
 the door allows you to store cable connectors inside drum to prevent damage to your valuable connectors during rolling up and off the cable drum
- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with locking brake screw
- spool made of special rubber
- powder-coated steel frame
- stackable with SK 380
- without cable
- transport trolley available as accessory
- drum-ø 380 mm

Order No.	Item	Version		Weight (kg)
403 29 000 000	SK 380.RMFK	with latching door (2 hinges)	RM-spool, flange hole ø 51 mm	6.03

SK 450.RMFK



- professional stage cable drum
- with latching door and RM-auxiliary spool with velcro strap
- the door ensures optimal protection of your high quality cable connectors;
 the door allows you to store cable connectors inside drum to prevent damage to your valuable connectors during rolling up and off the cable drum
- for storing and safely transporting all types of lines and wires for example pneumatic tubes, water hose, high pressure hoses, ropes, control and speciality cables
- with locking brake screw
- spool made of special rubber
- powder-coated steel frame
- stackable with SK 450
- without cable
- transport trolley available as accessory
- drum-ø 450 mm

Order No.	Item	Version		Weight (kg)
404 29 000 000	SK 450.RMFK	with latching door (2 hinges)	RM-spool, flange hole ø 51 mm	6.20



GT 450.MS6



- with 6-pin data slip ring for signal transmission
- · with junction box
- spool made of special rubber
- powder-coated steel carrying handle
- with locking brake screw
- without cable
- drum-ø 450 mm

Order No.	Item	Version	Weight (kg)
280 06 000 000	GT 450.MS6	with 6-pin data slip ring max. 2A	7.49



HT 300K.MS6



- with 6-pin data slip ring for signal transmission
- with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 141 mm

Order No.	Item	Version	Weight (kg)
331 06 000 000	HT 300K.MS6	with 6-pin data slip ring max. 2A	4.17

HT 305.MS6



- with 6-pin data slip ring for signal transmission
- with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 210 mm

Order No.	Item	Version	Weight (kg)
338 06 000 000	HT 305.MS6	with 6-pin data slip ring max. 2A	4.60



HT 380.MS6



- with 6-pin data slip ring for signal transmission
- with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 141 mm

Order No.	Item	Version	Weight (kg)
360 06 000 000	HT 380.MS6	with 6-pin data slip ring max. 2A	8.40

HT 385.MS6



- with 6-pin data slip ring for signal transmission
- with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 210 mm

Order No. Ite	em	Version	Weight (kg)
368 06 000 000 HT	T 385.MS6	with 6-pin data slip ring max. 2A	8.70



HT 485.MS6



- with 6-pin data slip ring for signal transmission
- with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 210 mm

Order No.	Item	Version	Weight (kg)
376 06 001 000	HT 485.MS6	with 6-pin data slip ring max. 2A	8.08



GT 450.MS12



- with 12-pin data slip ring for signal transmission
- with junction box
- spool made of special rubber
- powder-coated steel carrying handle
- with locking brake screw
- without cable
- drum-ø 450 mm

Order No.	Item	Version	Weight (kg)
280 12 000 000	GT 450.MS12	with 12-pin data slip ring max. 2A	7.49



HT 300K.MS12



- with 12-pin data commutator ring for signal transmission
- with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 141 mm

Order No.	Item	Version	Weight (kg)
331 12 000 000	HT 300K.MS12	with 12-pin data slip ring max. 2A	4.27

HT 305.MS12



- with 12-pin data slip ring for signal transmission
- with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 210 mm

Order No.	Item	Version	Weight (kg)
338 12 000 000	HT 305.MS12	with 12-pin data slip ring max. 2A	4.66



HT 380.MS12



- with 12-pin data slip ring for signal transmission
- with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 141 mm

Order No.	Item	Version	Weight (kg)
360 12 000 000	HT 380.MS12	with 12-pin data slip ring max. 2A	5.70

HT 385.MS12



- with 12-pin data slip ring for signal transmission
- with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 210 mm

Order No.	Item	Version	Weight (kg)
368 12 000 000	HT 385.MS12	with 12-pin data slip ring max. 2A	4.57



HT 480.MS12



- with 12-pin data slip ring for signal transmission
- with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 141 mm

Order No.	Item	Version	Weight (kg)
370 12 000 000	HT 480.MS12	with 12-pin data slip ring max. 2A	4.47

HT 485.MS12



- with 12-pin data slip ring for signal transmission
- with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 210 mm

Order No. Ite	em	Version	Weight (kg)
376 12 001 000 HT	T 485.MS12	with 12-pin data slip ring max. 2A	8.14



HT 300K.MS18



- with 18-pin data slip ring for signal transmission
- with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 141 mm

Order No.	Item	Version	Weight (kg)
331 81 000 000	HT 300K.MS18	with 18-pin data slip ring max. 2A	4.37

HT 305.MS18



- with 18-pin data slip ring for signal transmission
- with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 210 mm

Order No.	Item	Version	Weight (kg)
338 18 000 000	HT 305.MS18	with 18-pin data slip ring max. 2A	4.84



HT 385.MS18



- with 18-pin data slip ring for signal transmission
- · with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 210 mm

Order No.	Item	Version	Weight (kg)
368 18 000 000	HT 385.MS18	with 18-pin data slip ring max. 2A	4.57

HT 485.MS18



- with 18-pin data slip ring for signal transmission
- with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 210 mm

Order No.	Item	Version	Weight (kg)
376 18 001 000	HT 485.MS18	with 18-pin data slip ring max. 2A	8.32



HT 300K.MS24



- with 24-pin data slip ring for signal transmission
- · with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 141 mm

Order No.	Item	Version	Weight (kg)
331 42 000 000	HT 300K.MS24	with 24-pin data slip ring max. 2A	4.47

HT 305.MS24



- with 24-pin data slip ring for signal transmission
- with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 210 mm

Order No.	Item	Version	Weight (kg)
338 24 000 000	HT 305.MS24	with 24-pin data slip ring max. 2A	4.89



HT 380.MS24



- with 24-pin data slip ring for signal transmission
- with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 141 mm

Order No.	Item	Version	Weight (kg)
360 24 000 000	HT 380.MS24	with 24-pin data slip ring max. 2A	3.82

HT 385.MS24



- with 24-pin data slip ring for signal transmission
- with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 210 mm

Order No.	Item	Version	Weight (kg)
368 24 000 000	HT 385.MS24	with 24-pin data slip ring max. 2A	4.12



HT 485.MS24



- with 24-pin data slip ring for signal transmission
- with junction box
- powder-coated sheet steel discs
- powder-coated steel carrying handle
- core made of plastic
- with locking brake screw
- without cable
- core width 210 mm

Order No.	Item	Version	Weight (kg)
376 24 001 000	HT 485.MS24	with 24-pin data slip ring max. 2A	8.37



Patented cable rewind for GT 310



Upgrade for all GT 310 models.

Plastic add-on kit. Suitable for cable diameters approx. Ø 6 bis 14 mm. This patented innovation ensures the cable no longer requires manual guidance during winding. The cable winding competently performs this task and automatically neatly winds the cable layer by layer on the drum core. This ensures the capacity of the cable drum is always used to its full extent.

Order No.	Item	Version	Weight (kg)
270 99 000 000	Cable rewind	for GT 310	0.23

Drum-Bag for GT 310



Perfectly fitting for the GT 310. For a better protection of the cable and the whole drum.

Order No.	Item	Version	
270 99 000 010	Drum-Bag	for GT 310	
270 99 000 011	Drum-Bag plus	for GT 310	with additional storage



Travelling unit for GT 380 - GT 450



A convenient accessory for applications in a variety of locations. Comfortable handling, sturdy construction.

Upgrade attachment kit made from plastic high shock resistance and steel pipe handle. With height-adjustable steel tube handle. With 2 polyamide wheels, ø 140 mm. Easy mounting on drum handle, stable and safe transport.

Order No.	Item	Version	Weight (kg)
397 00 010 000	Travelling unit	for GT 380 and GT 450	2.50



Transport trolley for the SK 310 - SK 450 series



A practical accessory for use in all kinds of places.

With 4 steerable rollers, wheel diameter 125 mm, solid rubber tyres. Corners of the plate protected, fits for the SK 310-450.

Order No.	Item	Version	Weight (kg)
405 99 000 000	TW SK-310-380-450	without brake	10.80

Transport trolley for the SK 46 serie



A convenient accessory for applications in a variety of locations.

Comfortable handling, sturdy construction made of angle iron with black powder-coated surface, particularly impact and abrasion proof. With 2 control rollers and 2 fixed castors for heavy loads, solid rubber tyres, wheel diameter 100 mm, model 5 features brake (2 wheels with stopfix).

Order No.	item	Version	Weight (kg)
410 99 000 000	TW 4600	without brake	7.80
410 99 001 000	TW 4600.S	with brake	7.80
410 99 100 000	TW 4600B	wide	8.50
410 99 101 000	TW 4600B.S	wide, with brake	8.50
411 99 000 000	TW 4601	without brake	8.30
411 99 001 000	TW 4601.S	with brake	8.30
411 99 100 000	TW 4601B	wide	8.60
411 99 101 000	TW 4601B.S	wide, with brake	8.60
412 99 000 000	TW 4602	without brake	8.90
412 99 001 000	TW 4602.S	with brake	8.90
412 99 100 000	TW 4602B	wide	9.20
412 99 101 000	TW 4602B.S	wide, with brake	9.20



Transport trolley for the SK 47 / SK 48 series



A convenient accessory for applications in a variety of locations.

Comfortable handling, sturdy construction made of angle iron with black powder-coated surface, particularly impact and abrasion proof. With 2 control rollers and 2 fixed castors for heavy loads, solid rubber tyres, wheel diameter 100 mm, model S features brake (2 wheels with stopfix).

Order No.	Item	Version	Weight (kg)
432 99 000 000	TW 4700/4822	without brake	10.00
432 99 001 000	TW 4700/4822.S	with brake	10.00
433 99 000 000	TW 4701/4823	without brake	11.00
433 99 001 000	TW 4701/4823.S	with brake	11.00

Transport trolley custom-made product



On request special transport trolleys for SL, SK and PL can be manufactured. Transport trolley made of metal, 2 swivel castors and 2 fixed castors, with brake.

Technical details



Explanation of the symbols and abbreviated designations for SCHILL model series

Cable qualities

H05VV-F 3G1,5

2 3 4 5 6 7 8

1 Purpose H = harmonised cable

2 Nominal voltage V

05 = 300/500 V07 = 450/750 V

3 Insulation

V = PVC

R = natural or synthetic rubber

B = synthetic rubber

4 Cable sheath

V = PVC

R = natural or synthetic rubber

N = neoprene rubber

Q = polyurethane

5 Cable type

F = fine wires for flexible cables

6 Number of wires

7 Protective conductor

G = with green/yellow wire

8 Cable cross section

Schill cable designations

KK = H05VV-F

KG = H05RR-F

KS = H07RN-F

PU = H07BQ-F

(For PU cable standard cable colour yellow, cable printing possible)

Cable types

H05VV-F: Standard version for normal load. Suitable for indoor applications.

H05RR-F: Suitable for connecting devices where the cable is subject to light mechanical loads. Suitable for indoor applications.

H07RN-F: Suitable for connecting devices where the cable is subject to moderate mechanical loads, e.g. for devices in commercial and agricultural

work shops. Suitable for dry, damp or wet rooms and for constant use outdoors.

H07BQ-F: Suitable for connecting devices where the cable is subject to moderate mechanical loads and for connecting commercial or agricultural

devices, for example. Suitable for constant use outdoors.

Degrees of protection

Code digit 1 - protection against foreign bodies

IP0X	IP1X	IP2X	IP3X	IP4X	IP5X	IP6X
Not protected	Protected against foreign bodies > 50 mm	Protected against foreign bodies >12,5 mm	Protected against foreign bodies >2,5mm	Protected against foreign bodies >1mm	Protected against dust	Dust-proof
					*	

Technical details



Degrees of protection

Code digit 2 - protection against water

IPX0	IPX1	IPX2	IPX3	IPX4	IPX5	IPX6	IPX7	IPX8
Not protected	Protected against vertically dripping water	Protected against dripping water when tilted	Protected against spraying water	Protected against splashing water	Protected against water jets	Protected against powerful water jets	Protected against intermittent submersion*	Protected against continuous submersion
	•						& &	▲ ▲ m

^{*}For GT 310.WS3-IP67: Up to 1 meter water depth and for a maximum of 30 minutes (checked by TÜV-Süd)

Explanation of symbols



Complies with DGUV 203-006 and 203-005 Formerly BGI 608 and 600



Earthed socket Open



With thermal protection Thermal protection in accordance with VDE




Machine socket with self-closing hinged cover



With RCD Residual current device



CEE socket 3x16A with self-closing hinged cover





CEE socket 5x16A with self-closing hinged cover



CEE socket 5x32A with self-closing hinged cover

Protection classes



I: Protected by protective conductor connection, all conductive parts are connected to the earth potential



II: Protective insulation, reinforced or double insulation of the mains supply circuit

230V 16A Open earthed sockets Plastic









KB 210.S2



- with 2 open earthed sockets, 2-pin + E, 16A, 230V
- with thermal protection
- cable colour: white

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
140 02 310 000	KB 210.S2	II	IP20	10	H05VV-F 3G1,0	230V~/16A	1000W	2500W	1.25









KB 225.S2



- with 2 open earthed sockets, 2-pin + E, 16A, 230V
- with thermal protection
- cable colour: white

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
170 02 320 000	KB 225.S2	II	IP20	20	H05VV-F 3G1,0	230V~/16A	750W	2500W	2.15









KB 0515.S2



- with 2 open earthed sockets, 2-pin + E, 16A, 230V
- with thermal protection
- cable colour: white

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
140 02 315 000	KB 0515.S2	II	IP20	5	H05VV-F 3G1,5	230V~/16A	1200W	3600W	1.10







KB 1015.S4



- with 4 open earthed sockets, 2-pin + E, 16A, 230V
- with thermal protection
- cable colour: white

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
180 04 315 000	KB 1015.S4	II	IP20	10	H05VV-F 3G1,5	230V~/16A	1200W	3600W	1.94













- with 2 open earthed sockets, 2-pin + E, 16A, 230V
- with thermal protection
- particularly smooth-running
- cable colour: white

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
120 02 310 000	KB 170.S2	П	IP20	10	H05VV-F 3G1,0	230V~/16A	1000W	2500W	1.37









KB 220.S2



- with 2 open earthed sockets, 2-pin + E, 16A, 230V
- with thermal protection
- particularly smooth-running
- cable colour: white

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
150 02 320 000	KB 220.S2	II	IP20	20	H05VV-F 3G1,0	230V~/16A	750W	2500W	2.50

230V 16A Open earthed sockets Plastic









IT 220.S4



- with 4 open earthed sockets, 2-pin + E, 16A, 230V
- with thermal protection
- with locking brake screw
- carry handle made from galvanised steel tube with insulated handle

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
225 04 122 000	IT 220.S4.25KK315	II	IP20	25	H05VV-F 3G1,5	230V~/16A	1000W	3600W	3.94
225 04 322 000	IT 220.S4.25KG315	Ш	IP20	25	H05VV-F 3G1,5	230V~/16A	1000W	3600W	4.54











IT 280.S4



- with 4 open earthed sockets, 2-pin + E, 16A, 230V
- with thermal protection
- with locking brake screw
- carry handle made from galvanised steel tube with insulated handle

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
240 04 000 000	IT 280.S4					230V~/16A			1.40
240 04 122 000	IT 280.S4.25KK315	II	IP40	25	H05VV-F 3G1,5	230V~/16A	1500W	3600W	4.30
240 04 125 000	IT 280.S4.50KK315	II	IP40	50	H05VV-F 3G1,5	230V~/16A	1100W	3600W	6.20
240 04 322 000	IT 280.S4.25KG315	П	IP40	25	H05RR-F 3G1,5	230V~/16A	1500W	3600W	4.40
240 04 325 000	IT 280.S4.50KG315	II	IP40	50	H05RR-F 3G1,5	230V~/16A	1100W	3600W	7.90

230V 16A Open earthed sockets Sheet steel











HT 280.S4



- with 4 open earthed sockets, 2-pin + E, 16A, 230V
- with thermal protection
- with locking brake screw
- carry handle made from galvanised steel tube with insulated handle

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
320 04 000 000	HT 280.54					230V~/16A			2.40
320 04 122 000	HT 280.S4.25KK315	I	IP20	25	H05VV-F 3G1,5	230V~/16A	1500W	3600W	5.30
320 04 125 000	HT 280.S4.50KK315	ı	IP20	50	H05VV-F 3G1,5	230V~/16A	1100W	3600W	7.20
320 04 322 000	HT 280.S4.25KG315	I	IP20	25	H05RR-F 3G1,5	230V~/16A	1500W	3600W	5.40
320 04 325 000	HT 280.S4.50KG315	I	IP20	50	H05RR-F 3G1,5	230V~/16A	1100W	3600W	8.90

Voltage: Fittings: Material:

230V 16A
Earthed sockets with protection against dripping water











IT 280.TS4



- with 4 earthed sockets, 2-pin + E, 16A, 230V
- with protection against dripping water
- with thermal protection
- with locking brake screw
- carry handle made from galvanised steel tube with insulated handle

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
240 37 000 000	IT 280.TS4					230V~/16A			1.51
240 37 422 000	IT 280.TS4.25KS315	П	IP41	25	H07RN-F 3G1,5	230V~/16A	1500W	3600W	5.21
240 37 424 000	IT 280.TS4.40KS315	П	IP41	40	H07RN-F 3G1,5	230V~/16A	1200W	3600W	7.30
240 37 322 000	IT 280.TS4.25KG315	П	IP41	25	H05RR-F 3G1,5	230V~/16A	1500W	3600W	4.40
240 37 325 000	IT 280.TS4.50KG315	II	IP41	50	H05RR-F 3G1,5	230V~/16A	1100W	3600W	7.60
240 37 425 000	IT 280.TS4.50KS315	II	IP41	50	H07RN-F 3G1,5	230V~/16A	1100W	3600W	8.70

230V 16A
Earthed sockets with protection against dripping water
Sheet steel











HT 280.TS4



- with 4 earthed sockets, 2-pin + E, 16A, 230V
- with protection against dripping water
- with thermal protection
- with locking brake screw
- carry handle made from galvanised steel tube with insulated handle

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
320 37 000 000	HT 280.TS4					230V~/16A			2.50
320 37 422 000	HT 280.TS4.25KS315	I	IP40	25	H07RN-F 3G1,5	230V~/16A	1500W	3600W	6.20
320 37 424 000	HT 280.TS4.40KS315	ı	IP40	40	H07RN-F 3G1,5	230V~/16A	1200W	3600W	8.30
320 37 425 000	HT 280.TS4.50KS315	I	IP40	50	H07RN-F 3G1,5	230V~/16A	1100W	3600W	9.70
321 37 432 000	HT 280.TS4.25KS325	ı	IP40	25	H07RN-F 3G2,5	230V~/16A	2000W	3600W	7.95
320 37 322 000	HT 280.TS4.25KG315	ı	IP40	25	H05RR-F 3G1,5	230V~/16A	1500W	3600W	5.50
320 37 325 000	HT 280.TS4.50KG315	ı	IP40	50	H05RR-F 3G1,5	230V~/16A	1100W	3600W	8.17

230V 16A Earthed sockets with hinged cover Plastic













IT 300.TS3



- with 3 earthed sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with practical plug holder at the drum base

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
250 36 000 000	IT 300.TS3					230V~/16A			1.80
250 36 325 000	IT 300.TS3.50KG315	II	IP20	50	H05RR-F 3G1,5	230V~/16A	1000W	3600W	8.60
250 36 425 000	IT 300.TS3.50KS315	II	IP44	50	H07RN-F 3G1,5	230V~/16A	1000W	3600W	8.92
250 36 432 000	IT 300.TS3.25KS325	П	IP44	25	H07RN-F 3G2,5	230V~/16A	1900W	3600W	6.80
250 36 433 000	IT 300.TS3.33KS325	II	IP44	33	H07RN-F 3G2,5	230V~/16A	1700W	3600W	6.80

Earthed sockets with hinged cover











HT 260.TS3



- with 3 self-closing earthed sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
310 36 000 000	HT 260.TS3					230V~/16A			2.52
310 36 322 000	HT 260.TS3.25KG315	I	IP20	25	H05RR-F 3G1,5	230V~/16A	1300W	3220W	5.52
310 36 422 000	HT 260.TS3.25KS315	ı	IP20	25	H07RN-F 3G1,5	230V~/16A	1300W	3220W	6.12

230V 16A Machine sockets with hinged cover Plastic

















IT 266.MD3



- with 3 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with practical plug holder at the drum base
- complies with the requirements of the German Social Accident Insurance (DGUV),
- DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
230 40 000 000	IT 266.MD3					230V~/16A			1.48
230 40 122 000	IT 266.MD3.25KK315	II	IP20	25	H05VV-F 3G1,5	230V~/16A	1200W	3220W	3.90
230 40 125 000	IT 266.MD3.50KK315	II	IP20	50	H05VV-F 3G1,5	230V~/16A	1000W	3220W	6.30
230 40 322 000	IT 266.MD3.25KG315	II	IP20	25	H05RR-F 3G1,5	230V~/16A	1200W	3220W	4.50
230 40 325 000	IT 266.MD3.50KG315	II	IP20	50	H05RR-F 3G1,5	230V~/16A	1000W	3220W	7.50
230 40 422 000	IT 266.MD3.25KS315*	II	IP54	25	H07RN-F 3G1,5	230V~/16A	1200W	3220W	5.20
230 40 424 000	IT 266.MD3.40KS315*	II	IP54	40	H07RN-F 3G1,5	230V~/16A	1000W	3220W	7.30
230 40 432 000	IT 266.MD3.25KS325*	II	IP54	25	H07RN-F 3G2,5	230V~/16A	2000W	3220W	6.50
230 40 522 000	IT 266.MD3.25PU315*	II	IP54	25	H07BQ-F 3G1,5	230V~/16A	1200W	3220W	5.20
230 40 532 000	IT 266.MD3.25PU325*	II	IP54	25	H07BQ-F 3G2,5	230V~/16A	2000W	3220W	6.50

230V 16A Plastic

















IT 266.MD3L



- with 3 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with practical plug holder at the drum base
- with voltage indicator (L)
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
234 40 000 000	IT 266.MD3L					230V~/16A			1.32
234 40 122 000	IT 266.MD3L.25KK315	II	IP20	25	H05VV-F 3G1,5	230V~/16A	1200W	3220W	4.40
234 40 125 000	IT 266.MD3L.50KK315	II	IP20	50	H05VV-F 3G1,5	230V~/16A	1000W	3220W	6.70
234 40 322 000	IT 266.MD3L.25KG315	II	IP20	25	H05RR-F 3G1,5	230V~/16A	1200W	3220W	4.50
234 40 325 000	IT 266.MD3L.50KG315	II	IP20	50	H05RR-F 3G1,5	230V~/16A	1000W	3220W	7.00
234 40 422 000	IT 266.MD3L.25KS315	II	IP54	25	H07RN-F 3G1,5	230V~/16A	1200W	3220W	4.55
234 40 424 000	IT 266.MD3L.40KS315*	II	IP54	40	H07RN-F 3G1,5	230V~/16A	1000W	3220W	6.68
234 40 432 000	IT 266.MD3L.25KS325*	II	IP54	25	H07RN-F 3G2,5	230V~/16A	2000W	3220W	6.54

















GT 235.MD3



- with 3 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Note: A H07RN-F or H07BQ-F cable is required for use outdoors and in damp rooms.

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
200 40 000 000	GT 235.MD3					230V~/16A			1.17
200 40 122 000	GT 235.MD3.25KK315	II	IP20	25	H05VV-F 3G1,5	230V~/16A	1300W	3220W	3.58
200 40 322 000	GT 235.MD3.25KG315	Ш	IP20	25	H05RR-F 3G1,5	230V~/16A	1300W	3220W	4.17
200 40 422 000	GT 235.MD3.25KS315*	Ш	IP54	25	H07RN-F 3G1,5	230V~/16A	1300W	3220W	4.87
200 40 522 000	GT 235.MD3.25PU315*	II	IP54	25	H07BQ-F 3G1,5	230V~/16A	1300W	3220W	3.97











GT 235.MD3L



- with 3 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with voltage indicator (L)

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
204 40 000 000	GT 235.MD3L					230V~/16A			1.17
204 40 322 000	GT 235.MD3L.25KG315	II	IP20	25	H05RR-F 3G1,5	230V~/16A	1300W	3220W	4.17

















GT 310.MD4



- with 4 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with practical plug holder at the drum base
- optionally a version with child-proof machine sockets is also available
- complies with the requirements of the German Social Accident Insurance (DGUV),
- DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 42 000 000	GT 310.MD4					230V~/16A			1.97
270 42 422 000	GT 310.MD4.25KS315*	П	IP54	25	H07RN-F 3G1,5	230V~/16A	1500W	3600W	5.67
270 42 424 000	GT 310.MD4.40KS315*	II	IP54	40	H07RN-F 3G1,5	230V~/16A	1300W	3600W	7.77
270 42 425 000	GT 310.MD4.50KS315*	II	IP54	50	H07RN-F 3G1,5	230V~/16A	1250W	3600W	9.17
270 42 432 000	GT 310.MD4.25KS325*	II	IP54	25	H07RN-F 3G2,5	230V~/16A	2200W	3600W	6.97
270 42 433 000	GT 310.MD4.33KS325*	II	IP54	33	H07RN-F 3G2,5	230V~/16A	2000W	3600W	8.40
270 42 322 000	GT 310.MD4.25KG315	II	IP20	25	H05RR-F 3G1,5	230V~/16A	1500W	3600W	5.40
270 42 325 000	GT 310.MD4.50KG315	II	IP20	50	H05RR-F 3G1,5	230V~/16A	1250W	3600W	7.37
270 42 522 000	GT 310.MD4.25PU315*	II	IP54	25	H07BQ-F 3G1,5	230V~/16A	1500W	3600W	4.77
270 42 524 000	GT 310.MD4.40PU315*	II	IP54	40	H07BQ-F 3G1,5	230V~/16A	1300W	3600W	6.27
270 42 525 000	GT 310.MD4.50PU315*	II	IP54	50	H07BQ-F 3G1,5	230V~/16A	1250W	3600W	7.27
270 42 532 000	GT 310.MD4.25PU325*	II	IP54	25	H07BQ-F 3G2,5	230V~/16A	2200W	3600W	5.57
270 42 526 000	GT 310.MD4.40PU325*	II	IP54	40	H07BQ-F 3G2,5	230V~/16A	1800W	3600W	7.73















GT 310.MD4L



- with 4 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with practical plug holder at the drum base
- with voltage indicator (L)
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 44 000 000	GT 310.MD4L					230V~/16A			1.98
270 44 422 000	GT 310.MD4L.25KS315*	II	IP54	25	H07RN-F 3G1,5	230V~/16A	1500W	3600W	5.68
270 44 424 000	GT 310.MD4L.40KS315*	II	IP54	40	H07RN-F 3G1,5	230V~/16A	1300W	3600W	6.51
270 44 425 000	GT 310.MD4L.50KS315*	II	IP54	50	H07RN-F 3G1,5	230V~/16A	1250W	3600W	9.18
270 44 432 000	GT 310.MD4L.25KS325*	II	IP54	25	H07RN-F 3G2,5	230V~/16A	2200W	3600W	6.98
270 44 522 000	GT 310.MD4L.25PU315*	II	IP54	25	H07BQ-F 3G1,5	230V~/16A	1500W	3600W	4.78
270 44 524 000	GT 310.MD4L.40PU315*	II	IP54	40	H07BQ-F 3G1,5	230V~/16A	1300W	3600W	6.28
270 44 525 000	GT 310.MD4L.50PU315*	II	IP54	50	H07BQ-F 3G1,5	230V~/16A	1250W	3600W	7.28
270 44 532 000	GT 310.MD4L.25PU325*	II	IP54	25	H07BQ-F 3G2,5	230V~/16A	2200W	3600W	5.58















GT 310.MD5



- with 5 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with practical plug holder at the drum base
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 46 000 000	GT 310.MD5					230V~/16A			2.01
270 46 422 000	GT 310.MD5.25KS315*	II	IP54	25	H07RN-F 3G1,5	230V~/16A	1500W	3600W	5.71
270 46 424 000	GT 310.MD5.40KS315*	II	IP54	40	H07RN-F 3G1,5	230V~/16A	1300W	3600W	7.81
270 46 425 000	GT 310.MD5.50KS315*	II	IP54	50	H07RN-F 3G1,5	230V~/16A	1250W	3600W	9.21
270 46 432 000	GT 310.MD5.25KS325*	II	IP54	25	H07RN-F 3G2,5	230V~/16A	2200W	3600W	4.81
270 46 522 000	GT 310.MD5.25PU315*	II	IP54	25	H07BQ-F 3G1,5	230V~/16A	1500W	3600W	5.93
270 46 524 000	GT 310.MD5.40PU315*	II	IP54	40	H07BQ-F 3G1,5	230V~/16A	1300W	3600W	6.31
270 46 525 000	GT 310.MD5.50PU315*	II	IP54	50	H07BQ-F 3G1,5	230V~/16A	1250W	3600W	7.31













GT 310.MD5L



- with 5 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with practical plug holder at the drum base
- with voltage indicator (L)
- complies with the requirements of the German Social Accident Insurance (DGUV),
- DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Note: A H07RN-F or H07BQ-F cable is required for use outdoors and in damp rooms.

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 47 000 000	GT 310.MD5L					230V~/16A			2.02
270 47 425 000	GT 310.MD5L.50KS315*	П	IP54	50	H07RN-F 3G1,5	230V~/16A	1250W	3600W	9.22
270 47 525 000	GT 310.MD5L.50PU315*	II	IP54	50	H07BQ-F 3G1,5	230V~/16A	1250W	3600W	7.32

GT 380.MD6















- with 6 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
275 48 000 000	GT 380.MD6					230V~/16A			4.50
275 48 435 000	GT 380.MD6.50KS325*	II	IP54	50	H07RN-F 3G2,5	230V~/16A	1500W	3600W	14.10
275 48 525 000	GT 380.MD6.50PU315*	П	IP54	50	H07BQ-F 3G1,5	230V~/16A	1250W	3600W	9.80
275 48 535 000	GT 380.MD6.50PU325*	II	IP54	50	H07BQ-F 3G2,5	230V~/16A	1500W	3600W	12.30















GT 380.MD6L



- with 6 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with voltage indicator (L)
- complies with the requirements of the German Social Accident Insurance (DGUV),
- DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Note: A H07RN-F or H07BQ-F cable is required for use outdoors and in damp rooms.

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
275 50 000 000	GT 380.MD6L					230V~/16A			4.51
275 50 435 000	GT 380.MD6L.50KS325*	П	IP54	50	H07RN-F 3G2,5	230V~/16A	1500W	3600W	14.11
275 50 535 000	GT 380.MD6L.50PU325*	II	IP54	50	H07BQ-F 3G2,5	230V~/16A	1500W	3600W	12.31













GT 450.MD5



- with 5 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
280 42 000 000	GT 450.MD5					230V~/16A			5.89
280 42 435 000	GT 450.MD5.50KS325*	П	IP54	50	H07RN-F 3G2,5	230V~/16A	1850W	3600W	15.49
280 42 535 000	GT 450.MD5.50PU325*	II	IP44	50	H07BQ-F 3G2,5	230V~/16A	1850W	3600W	13.69



HT 311.MD3















- with 3 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with practical plug holder at the drum base

Note: A H07RN-F or H07BQ-F cable is required for use outdoors and in damp rooms.

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
350 40 000 000	HT 311.MD3					230V~/16A			2.70
350 40 125 000	HT 311.MD3.50KK315	- 1	IP40	50	H05VV-F 3G1,5	230V~/16A	1100W	3220W	7.50
350 40 322 000	HT 311.MD3.25KG315	I	IP40	25	H05RR-F 3G1,5	230V~/16A	1500W	3220W	5.70
350 40 325 000	HT 311.MD3.50KG315	I	IP40	50	H05RR-F 3G1,5	230V~/16A	1100W	3220W	9.20
350 40 422 000	HT 311.MD3.25KS315	I	IP54	25	H07RN-F 3G1,5	230V~/16A	1500W	3220W	6.40
350 40 424 000	HT 311.MD3.40KS315	1	IP54	40	H07RN-F 3G1,5	230V~/16A	1300W	3220W	8.50
350 40 425 000	HT 311.MD3.50KS315	I	IP54	50	H07RN-F 3G1,5	230V~/16A	1100W	3220W	9.90
350 40 432 000	HT 311.MD3.25KS325	I	IP54	25	H07RN-F 3G2,5	230V~/16A	2200W	3220W	7.70











HT 305.MD4



- with 4 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
333 42 000 000	HT 305.MD4					230V~/16A			4.30
333 42 435 000	HT 305.MD4.50KS325	I	IP54	50	H07RN-F 3G2,5	230V~/16A	1500W	3600W	14.10











HT 305.MD4L



- with 4 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with voltage indicator (L)

Note: A H07RN-F or H07BQ-F cable is required for use outdoors and in damp rooms.

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
333 44 000 000	HT 305.MD4L					230V~/16A			3.52
333 44 435 000	HT 305.MD4L50KS325	I	IP54	50	H07RN-F 3G2,5	230V~/16A	1500W	3600W	14.20

HT 305.MD5











- with 5 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
333 46 000 000	HT 305.MD5					230V~/16A			4.39
333 46 435 000	HT 305.MD5.50KS325	I	IP54	50	H07RN-F 3G2,5	230V~/16A	1500W	3600W	14.20













HT 305.MD5L



- with 5 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with voltage indicator (L)

Note: A H07RN-F or H07BQ-F cable is required for use outdoors and in damp rooms.

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
333 48 000 000	HT 305.MD5L					230V~/16A			4.40
333 48 435 000	HT 305.MD5L.50KS325	- I	IP54	50	H07RN-F 3G2,5	230V~/16A	1500W	3600W	14.30













HT 380.MD4

- with 4 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
360 42 000 000	HT 380.MD4					230V~/16A			5.50
360 42 435 000	HT 380.MD4.50KS325	I	IP40	50	H07RN-F 3G2,5	230V~/16A	1500W	3600W	15.10

230V 16A Machine sockets with hinged cove. Sheet steel















- with 4 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with voltage indicator (L)

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
360 44 000 000	HT 380.MD4L					230V~/16A			5.51
360 44 435 000	HT 380.MD4L.50KS325	I	IP40	50	H07RN-F 3G2,5	230V~/16A	1500W	3600W	15.11

HT 380.MD5













- with 5 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
360 46 000 000	HT 380.MD5					230V~/16A			5.41
360 46 435 000	HT 380.MD5.50KS325	I	IP40	50	H07RN-F 3G2,5	230V~/16A	1500W	3600W	16.52

230V 16A Machine sockets with hinged cove. Sheet steel













HT 380.MD5L



- with 5 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with voltage indicator (L)

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
360 48 000 000	HT 380.MD5L					230V~/16A			5.41
360 48 435 000	HT 380.MD5L.50KS325	I	IP40	50	H07RN-F 3G2,5	230V~/16A	1500W	3600W	16.52







HT 480.MD4



- with 4 earthed machine sockets, 2-pin + E, 16A, 230V
- · with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
370 42 000 000	HT 480.MD4					230V~/16A			7.52

230V 16A Machine sockets with hinged cove Sheet steel









HT 480.MD4L



- with 4 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with voltage indicator (L)

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
370 44 000 000	HT 480.MD4L					230V~/16A			7.60

HT 480.MD5









- with 5 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
370 46 000 000	HT 480.MD5					230V~/16A			7.56

Voltage: Fittings: Material: 230V 16A Machine sockets with hinged cove Shoot stool









HT 480.MD5L



- with 5 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with voltage indicator (L)

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
370 48 000 000	HT 480.MD5L					230V~/16A			7.57

230V 16A Machine sockets resistant to pressurised water Special rubber



GT 310.WS1















- suitable for wet areas
- with 1 earthed socket which is resistant to pressurised water, 2-pin + E, 16A, 230V (IP68)
- with bayonet closure
- with thermal protection
- with locking brake screw
- when fi tted with cable, includes plug which is resistant to pressurised water at the end of
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 31 000 000	GT 310.WS1					230V~/16A			2.06
270 31 422 000	GT 310.WS1.25KS315*	II	IP55	25	H07RN-F 3G1,5	230V~/16A	1500W	3600W	5.76
270 31 424 000	GT 310.WS1.40KS315*	II	IP55	40	H07RN-F 3G1,5	230V~/16A	1300W	3600W	6.30
270 31 425 000	GT 310.WS1.50KS315*	II	IP55	50	H07RN-F 3G1,5	230V~/16A	1250W	3600W	9.26



GT 310.WS3















- suitable for wet areas
- with 1 earthed socket which is resistant to pressurised water, 2-pin + E, 16A, 230V (IP68)
- with bayonet closure
- with thermal protection
- with locking brake screw
- when fitted with cable, includes plug which is resistant to pressurised water at the end of
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 35 000 000	GT 310.WS3					230V~/16A			2.06
270 35 422 000	GT 310.WS3.25KS315*	II	IP55	25	H07RN-F 3G1,5	230V~/16A	1500W	3600W	5.76
270 35 425 000	GT 310.WS3.50KS315*	II	IP55	50	H07RN-F 3G1,5	230V~/16A	1250W	3600W	9.26
270 35 432 000	GT 310.WS3.50KS315*	II	IP55	25	H07RN-F 3G2,5	230V~/16A	2200W	3600W	7.06
270 35 522 000	GT 310.WS3.50KS315*	II	IP55	25	H07BQ-F 3G1,5	230V~/16A	1500W	3600W	4.86
270 35 524 000	GT 310.WS3.40PU315*	II	IP55	40	H07BQ-F 3G1,5	230V~/16A	1300W	3600W	6.30
270 35 525 000	GT 310.WS3.50PU315*	II	IP55	50	H07BQ-F 3G1,5	230V~/16A	1250W	3600W	7.36
270 35 532 000	GT 310.WS3.25PU325*	II	IP55	25	H07BQ-F 3G2,5	230V~/16A	2200W	3600W	5.66
270 35 526 000	GT 310.WS3.40PU325*	II	IP55	40	H07BQ-F 3G2,5	230V~/16A	1800W	3600W	8.15













GT 310.WS3-IP67 NEW



- suitable for wet areas
- with 3 earthed sockets which are resistant to pressurised water, 2-pin + E, 16A, 230V (IP68)
- with bayonet closure
- with thermal protection
- with locking brake screw
- with plug which is resistant to pressurised water at the end of the cable
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Our new **GT 310.WS3-IP67** (patent application submitted) has IP67 protection for the entire drum and is therefore ideal for safe use in wet areas. Intermittent submersion* of the entire drum body therefore no longer presents a risk for people or the environment.

Application areas for this extremely robust special rubber cable drum include emergency workers (fire services, technical relief workers, disaster response workers), mining, military, shipbuilding, etc.



Plug which is resistant to pressurised water fitted at the end of the cable



Cover with 3 earthed sockets which are resistant to pressurised water

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 67 422 000	GT 310.WS3.25KS315-IP67*	II	IP67	25	H07RN-F 3G1,5	230V~/16A	1250W	3600W	5.76
270 67 424 000	GT 310.WS3.40KS315-IP67*	II	IP67	40	H07RN-F 3G1,5	230V~/16A	1250W	3600W	7.86
270 67 425 000	GT 310.WS3.50KS315-IP67*	II	IP67	50	H07RN-F 3G1,5	230V~/16A	1250W	3600W	9.26

Voltage: Fittings: Material: 230V 16A Machine sockets resistant to pressurised water Special rubber















GT 380.WS4



- suitable for wet areas
- with 4 earthed sockets which are resistant to pressurised water, 2-pin + E, 16A, 230V (IP68)
- with bayonet closure
- with thermal protection
- with locking brake screw
- when fitted with cable, includes plug which is resistant to pressurised water at the end of
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
275 34 000 000	GT 380.WS4					230V~/16A			4.60
275 34 425 000	GT 380.WS4.50KS315	II	IP55	50	H07RN-F 3G1,5	230V~/16A	1250W	3600W	11.80
275 34 435 000	GT 380.WS4.50KS325*	II	IP55	50	H07RN-F 3G2,5	230V~/16A	1500W	3600W	14.20
275 34 525 000	GT 380.WS4.50PU315*	II	IP55	50	H07BQ-F 3G1,5	230V~/16A	1250W	3600W	9.90
275 34 535 000	GT 380.WS4.50PU325*	II	IP55	50	H07BQ-F 3G2,5	230V~/16A	1500W	3600W	12.40



HT 300K.WS3





- with 3 earthed sockets which are resistant to pressurised water, 2-pin + E, 16A, 230V
- with bayonet closure
- with thermal protection
- with locking brake screw
- when fitted with cable, includes plug which is resistant to pressurised water at the end of the cable

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
331 35 000 000	HT 300K.WS3					230V~/16A			3.34
331 35 432 000	HT 300K.WS3.25KS325	T.	IP54	25	H07RN-F 3G2,5	230V~/16A	1900W	3600W	8.60
331 35 433 000	HT 300K.WS3.33KS325	I	IP54	33	H07RN-F 3G2,5	230V~/16A	1700W	3600W	10.70

HT 380.WS3











- with 3 earthed sockets which are resistant to pressurised water, 2-pin + E, 16A, 230V
- with bayonet closure
- with thermal protection
- with locking brake screw
- when fitted with cable, includes plug which is resistant to pressurised water at the end of the cable

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
360 35 000 000	HT 380.WS3					230V~/16A			6.12
360 35 435 000	HT 380.WS3.50KS325	I	IP40	50	H07RN-F 3G2,5	230V~/16A	1500W	3600W	16.12

Voltage: Fittings: Material: 230V 16A

Machine sockets, belg./french version, with hinged cover











IT 266.MD3B



- Belgian/French version
- with 3 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with practical plug holder at the drum base
- also available with optional voltage indicator

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
230 93 000 000	IT 266.MD3B					230V~/16A			1.40
230 93 122 000	IT 266.MD3B.25KK315	II	IP20	25	H05VV-F 3G1,5	230V~/16A	1200W	3220W	4.40
230 93 325 000	IT 266.MD3B.50KG315	II	IP20	50	H05RR-F 3G1,5	230V~/16A	1000W	3220W	7.00

230V 16A
Machine sockets, belg. / french version, with hinged cover
Special rubber

















GT 235.MD3B



- Belgian/French version
- with 3 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- complies with the requirements of the German Social Accident Insurance (DGUV),
- DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Note: A H07RN-F or H07BQ-F cable is required for use outdoors and in damp rooms.

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
200 93 000 000	GT 235.MD3B					230V~/16A			1.18
200 93 322 000	GT 235.MD3B.25KG315	II	IP20	25	H05RR-F 3G1,5	230V~/16A	1300W	3220W	2.28
200 93 422 000	GT 235.MD3B.25KS315*	II	IP54	25	H07RN-F 3G1,5	230V~/16A	1300W	3220W	2.28



















- Belgian/French version
- with 4 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with practical plug holder at the drum base
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 93 000 000	GT 310.MD4B					230V~/16A			2.10
270 93 325 000	GT 310.MD4B.50KG315	II	IP20	50	H05RR-F 3G1,5	230V~/16A	1250W	3600W	7.37
270 93 422 000	GT 310.MD4B.25KS315*	II	IP54	25	H07RN-F 3G1,5	230V~/16A	1500W	3600W	6.10















GT 310.MD4L.B



- Belgian/French version
- with 4 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with practical plug holder at the drum base
- with voltage indicator (L)
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Note: A H07RN-F or H07BQ-F cable is required for use outdoors and in damp rooms.

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 94 000 300	GT 310.MD4L.B					230V~/16A			2.20
270 94 432 000	GT 310.MD4L.B.25KS325*	II	IP54	25	H07RN-F 3G2,5	230V~/16A	2200W	3600W	6.60

GT 310.MD5L.B









- Belgian/French version
- with 5 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with practical plug holder at the drum base
- with voltage indicator (L)

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 95 000 000	GT 310.MD5L.B					230V~/16A			2.20















GT 310.3C316



- with 3 CEE socket, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with practical plug holder at the drum base
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Note: A H07RN-F or H07BQ-F cable is required for use outdoors and in damp rooms.

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 11 000 000	GT 310.3C316					230V~/16A			2.04
270 11 422 000	GT 310.3C316.25KS315*	II	IP54	25	H07RN-F 3G1,5	230V~/16A	1500W	3600W	5.74
270 11 425 000	GT 310.3C316.50KS315*	П	IP54	50	H07RN-F 3G1,5	230V~/16A	1250W	3600W	9.24
270 11 432 000	GT 310.3C316.25KS325*	П	IP54	25	H07RN-F 3G2,5	230V~/16A	2200W	3600W	7.04
270 11 532 000	GT 310.3C316.25PU325*	II	IP54	25	H07BQ-F 3G2,5	230V~/16A	2200W	3600W	5.74















GT 310.2C316MD1



- with 2 CEE sockets, 2-pin + E, 16A, 230V
- with 1 earthed machine socket, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with practical plug holder at the drum base
- suitable for use on campsites and boats
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 20 000 000	GT 310.2C316MD1					230V~/16A			2.20
270 20 422 000	GT 310.2C316MD1.25KS315*	II	IP54	25	H07RN-F 3G1,5	230V~/16A	1250W	3600W	5.74
270 20 432 000	GT 310.2C316MD1.25KS325*	II	IP54	25	H07RN-F 3G2,5	230V~/16A	2200W	3600W	8.20

CEE sockets

















GT 310.C316MD3



- with 1 CEE socket, 2-pin + E, 16A, 230V
- with 3 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with practical plug holder at the drum base
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 17 000 000	GT 310.C316MD3					230V~/16A			2.04
270 17 422 000	GT 310.C316MD3.25KS315*	II	IP54	25	H07RN-F 3G1,5	230V~/16A	1500W	3600W	5.74
270 17 425 000	GT 310.C316MD3.50KS315*	II	IP54	50	H07RN-F 3G1,5	230V~/16A	1250W	3600W	9.24
270 17 432 000	GT 310.C316MD3.25KS325*	II	IP54	25	H07RN-F 3G2,5	230V~/16A	2200W	3600W	7.04
270 17 433 000	GT 310.C316MD3.33KS325*	II	IP54	33	H07RN-F 3G2,5	230V~/16A	2000W	3600W	8.40













HT 300K.3C316



- with 3 CEE sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Note: A H07RN-F or H07BQ-F cable is required for use outdoors and in damp rooms.

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
331 11 000 000	HT 300K.3C316					230V~/16A			3.54
331 11 422 000	HT 300K.3C316.25KS315	1	IP54	25	H07RN-F 3G1,5	230V~/16A	1500W	3600W	9.00
331 11 432 000	HT 300K.3C316.25KS325	I	IP54	25	H07RN-F 3G2,5	230V~/16A	1900W	3600W	8.60

HT 300K.C316MD3













- with 1 CEE socket, 2-pin + E, 16A, 230V
- with 3 earthed machine sockets, 2-pin + E, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
331 17 000 000	HT 300K.C316MD3					230V~/16A			3.40
331 17 422 000	HT 300K.C316MD3.25KS315	I	IP54	25	H07RN-F 3G1,5	230V~/16A	1500W	3600W	7.10
331 17 425 000	HT 300K.C316MD3.50KS315	I	IP54	50	H07RN-F 3G1,5	230V~/16A	1000W	3600W	11.40

230V 16A Special rubber

















GT 310.FI.MD3



- with residual current device, 25A / 30mA, 0.03sec
- with 3 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with practical plug holder at the drum base
- complies with the requirements of the German Social Accident Insurance (DGUV),
- DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 57 000 000	GT 310.FI.MD3					230V~/16A			2.25
270 57 422 000	GT 310.FI.MD3.25KS315*	II	IP54	25	H07RN-F 3G1,5	230V~/16A	1500W	3600W	5.95
270 57 424 000	GT 310.FI.MD3.40KS315*	II	IP54	40	H07RN-F 3G1,5	230V~/16A	1300W	3600W	9.30
270 57 425 000	GT 310.FI.MD3.50KS315*	II	IP54	50	H07RN-F 3G1,5	230V~/16A	1250W	3600W	9.45
270 57 432 000	GT 310.FI.MD3.25KS325*	II	IP54	25	H07RN-F 3G2,5	230V~/16A	2200W	3600W	7.25
270 57 522 000	GT 310.FI.MD3.25PU315*	II	IP54	25	H07BQ-F 3G1,5	230V~/16A	1500W	3600W	4.70
270 57 525 000	GT 310.FI.MD3.50PU315*	II	IP54	50	H07BQ-F 3G1,5	230V~/16A	1250W	3600W	7.55
270 57 532 000	GT 310.FI.MD3.25PU325*	II	IP54	25	H07BQ-F 3G2,5	230V~/16A	2200W	3600W	5.85

230V 16A Special rubber

















GT 310.FI.2C316



- with residual current device, 25A / 30mA, 0.03sec
- with 2 CEE sockets, 2-pin + E, 16A
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Note: A H07RN-F or H07BQ-F cable is required for use outdoors and in damp rooms.

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 60 000 000	GT 310.Fl.2C316					230V~/16A			2.16
270 60 425 000	GT 310.FI.2C316.50KS315*	II	IP54	50	H07RN-F 3G1,5	230V~/16A	1250W	3600W	9.60
270 60 432 000	GT 310.FI.2C316.25KS325*	П	IP54	25	H07RN-F 3G2,5	230V~/16A	2200W	3600W	7.75













GT 450.FI.MD5



- with residual current device, 40A / 30mA, 0.03sec
- with 5 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
280 58 000 000	GT 450.FI.MD5					230V~/16A			7.35
280 58 465 000	GT 450.FI.MD5.50KS525*	II	IP54	50	H07RN-F 5G2,5	230V~/16A	1800W	3600W	25.00



HT 381.FI.MD3











- with residual current device, 25A / 30mA, 0.03sec
- with 3 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
362 57 000 000	HT 381.FI.MD3					230V~/16A			6.27
362 57 432 000	HT 381.FI.MD3.25KS325	I	IP40	25	H07RN-F 3G2,5	230V~/16A	2200W	3600W	11.27
362 57 425 000	HT 381.FI.MD3.50KS315	I	IP40	50	H07RN-F 3G1,5	230V~/16A	1300W	3600W	13.47
362 57 422 000	HT 381.FI.MD3.25KS315	- I	IP40	25	H07RN-F 3G1,5	230V~/16A	2000W	3600W	9.97
362 57 435 000	HT 381.FI.MD3.50KS325	ı	IP40	50	H07RN-F 3G2,5	230V~/16A	1800W	3600W	15.87







HT 381.FI.MD3B



- Belgian/French version
- with residual current device, 25A / 30mA, 0.03sec
- with 3 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
362 93 000 000	HT 381.FI.MD3B					230V~/16A			6.32













GT 310.SZ.MD3



- with 3 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with AC meter
- with thermal protection
- with locking brake screw
- with practical plug holder at the drum base
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*
- Note: A H07RN-F or H07BQ-F cable is required for use outdoors and in damp rooms.

The GT 310.SZ.MD3 is a particularly robust model made from unbreakable, chemical-resistant special rubber. It has an AC meter which only measures the energy that is actually used. However, the AC meter is approved for self-monitoring purposes only and not for energy billing.



AC meter

- Accuracy class B (1%)
- Direct measurements, uncalibrated
- Illuminated digital display with 7 digits, 2 of which are decimal places
- Energy consumption is stored in a non-volatile manner
- With voltage indicator

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 34 000 000	GT 310.SZ.MD3					230V~/16A			1.97
270 34 422 000	GT 310.SZ.MD3.25KS315*	Ш	IP54	25	H07RN-F 3G1,5	230V~/16A	1500W	3600W	5.76
270 34 424 000	GT 310.SZ.MD3.40KS315*	II	IP54	40	H07RN-F 3G1,5	230V~/16A	1300W	3600W	8.23
270 34 432 000	GT 310.SZ.MD3.25KS325*	II	IP54	25	H07RN-F 3G2,5	230V~/16A	2200W	3600W	6.97

230V 16A PRCD-S Special rubber















GT 310.MD4L-PRCD-S



Mobile personal protection

- with 4 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- · with practical plug holder at the brake screw
- with voltage indicator (L)
- complies with the requirements of the German Social Accident Insurance (DGUV),
- DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

The PRCD-S (Personal Residual Current Device - Safety) enables current to be drawn safely from on-site sockets.

The PRCD-S checks sockets – especially the protective conductors – to ensure that they are working properly and only allows current to be drawn from safe sockets.

The personal protection safety plug is the portable protective device for all construction and assembly sites in accordance with the requirements of the professional associations, the German Federal Ministry for Labour and Social Affairs and the accident prevention regulation of the fire services.



Overview of PRCD-S

- Residual current device (RCD)
- Protective conductor detection (checking function prior to operation)
- Protective conductor monitoring (checking function during operation)
- External voltage detection
- Undervoltage tripping function

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 44 422 430	GT 310.MD4L.25KS315-PRCDS*	II	IP54	25	H07RN-F 3G1,5	230V~/16A	1500W	3600W	5.68
270 44 424 430	GT 310.MD4L.40KS315-PRCDS*	II	IP54	40	H07RN-F 3G1,5	230V~/16A	1300W	3600W	6.51
270 44 522 430	GT 310.MD4L.25PU315-PRCDS*	II	IP54	25	H07BQ-F 3G1,5	230V~/16A	1500W	3600W	4.78
270 44 524 430	GT 310.MD4L.40PU315-PRCDS*	II	IP54	40	H07BQ-F 3G1,5	230V~/16A	1250W	3600W	6.28

230V 16A LED Special rubber











GT 310.LED



- special rubber cable drum with 1 7W LED light + on/off switch
- with 3 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- thermal protection
- with locking brake screw
- with practical plug holder at the drum base

This innovative product solution really packs a punch.

Thanks to the integrated LED light, there is no need for an additional light source when working in dark places. The cable drum itself can illuminate the work area perfectly at the touch of a button.

When it comes to electrical connections, the LED drum has 3 sockets to prevent users having to rethink the connection options when using several devices. A thermal switch protects against overheating and resulting damage to the drum. And of course, the LED drum is equipped with a rotating hand crank and a parking brake. The LED cable drum is a real ray of light when working in dark places.



- 7W branded LED, luminous flux 400lm
- Colour temperature 2800k
- Very bright, no heat development
- Radiation angle 36°
- GU10 thread
- Energy class A
- Service life approx. 40,000 hours

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 59 000 000	GT 310.LED.MD3					230V~/16A			1.97
270 59 322 000	GT 310.LED.MD3.25KG315		IP40	25	H05RR-F 3G1,5	230V~/16A	1500W	3600W	5.40
270 59 325 000	GT 310.LED.MD3.50KG315		IP40	50	H05RR-F 3G1,5	230V~/16A	1250W	3600W	7.37

Voltage: Fittings: Material: 230V 16A Flat slip ring Plastic





IT 300K.MS3



- slip ring drum with double contacting
- with 3-pole flat slip ring, 16A
- with 1,5 m H05RR-F 3G1.5 connection cable
- with steel tube handle
- with locking brake screw

Order No.	Item	Cable type	Version	Weight (kg)
260 31 000 000	IT 300K.MS3		3-pole slip ring, 16A	2.50

230V 16A Flat slip ring Special rubber





GT 450.MS3



- slip ring drum with double contacting
- with 3-pole flat slip ring, 16A
- with 1,5 m H05RR-F 3G1.5 connection cable
- with locking protection
- with lockable brake screw

Order No.	Item	Cable type	Version	Weight (kg)	
280 31 000 000	GT 450.MS3		3-pole slip ring, 16A	7.49	

Voltage: Fittings: Material: 230V 16A Flat slip ring Sheet steel



HT 582.MS3



- slip ring drum with double contacting
- with 3-pole flat slip ring 16A
- with 1,5 m connection cable H05RR-F 3G1,5
- with locking brake screw

Order No.	Item	Cable type	Version	Weight (kg)
379 31 000 000	HT 582.MS3		3-pole slip ring, 16A	12.98

230V 16A Flat slip ring Sheet steel





SK 4822.MS3.16



- slip ring drum with double contacting
- stackable construction cable drum
- with 3-pole slip ring, 16A
- with locking brake screw

Order No.	Item	Cable type	Version	Weight (kg)
432 34 000 000	SK 4822.MS3.16		3-pole slip ring, 16A	17.50

Voltage: Voltage: Material:



SK 4823.MS3.25



- slip ring drum with double contacting with 3 high-quality 25A brush slip rings
- stackable construction cable drum
- with locking brake screw

Order No.	Item	Cable type	Version	Weight (kg)	
433 31 000 000	SK 4823.MS3.25		3-pole slip ring, 25A	18.60	

230V 40A Flat slip ring Sheet steel



SK 4823.MS3.40



- slip ring drum with double conacting
- high-quality 40A brush slip rings
- stackable construction cable drum
- with locking brake screw

Order No.	Item	Cable type	Version	Weight (kg)
433 31 000 500	SK 4823.MS3.40		3-pole slip ring, 40A	22.00

















GT 310.C516MD3



- with 2 CEE sockets, 4-pin + E, 16A, 400V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 18 000 000	GT 310.C516MD3					230V~/16A 400V~/16A			2.14
270 18 452 000	GT 310.C516MD3.25KS515*	II	IP54	25	H07RN-F 5G1,5	230V~/16A 400V~/16A	1800W 4150W	3600W 11kW	7.54
270 18 462 000	GT 310.C516MD3.25KS525*	II	IP54	25	H07RN-F 5G2,5	230V~/16A 400V~/16A	2200W 5500W	3600W 11kW	9.84
270 18 552 000	GT 310.C516MD3.25PU515*	II	IP54	25	H07BQ-F 5G1,5	230V~/16A 400V~/16A	1800W 4150W	3600W 11kW	5.84
270 18 562 000	GT 310.C516MD3.25PU525*	II	IP54	25	H07BQ-F 5G2,5	230V~/16A 400V~/16A	2200W 5500W	3600W 11kW	8.54













GT 310.2C516



- with 2 CEE-sockets, 4-pin + E, 16A, 400V
- wiht self-closing hinged covers
- with thermal protection
- with locking brake screw
- complies with the requirements of the German Social Accident Insurance DGUV, DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 09 000 000	GT 310.2C516					400V~/16A			2.20
270 09 452 000	GT 310.2C516.25KS515*	II	IP54	25	H07RN-F 5G1,5	400V~/16A	4150W	11kW	7.35
270 09 462 000	GT 310.2C516.25KS525*	П	IP54	25	H07RN-F 5G2,5	400V~/16A	5500W	11 kW	9.78

















GT 310.2C516MD1



- with 2 CEE sockets, 4-pin + E, 16A, 400V
- with 1 earthed machine socket, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- complies with the requirements of the German Social Accident Insurance (DGUV),
- DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
270 21 000 000	GT 310.2C516MD1					230V~/16A 400V~/16A			2.15
270 21 452 000	GT 310.2C516MD1.25KS515*	II	IP54	25	H07RN-F 5G1,5	230V~/16A 400V~/16A	1800W 4150W	3600W 11kW	7.55
270 21 462 000	GT 310.2C516MD1.25KS525*	II	IP54	25	H07RN-F 5G2,5	230V~/16A 400V~/16A	2200W 5500W	3600W 11kW	9.85
270 21 552 000	GT 310.2C516MD1.25PU515*	II	IP54	25	H07BQ-F 5G1,5	230V~/16A 400V~/16A	1800W 4150W	3600W 11kW	5.85
270 21 562 000	GT 310.2C516MD1.25PU525*	II	IP54	25	H07BQ-F 5G2,5	230V~/16A 400V~/16A	2200W 5500W	3600W 11kW	8.55

















GT 380.2C516MD4



- with 2 CEE sockets, 4-pin + E, 16A, 400V
- with 4 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
275 20 000 000	GT 380.2C516MD4					230V~/16A 400V~/16A			4.72
275 20 455 000	GT 380.2C516MD4.50KS515*	II	IP54	50	H07RN-F 5G1,5	230V~/16A 400V~/16A	1250W 3000W	3600W 11kW	15.32
275 20 463 000	GT 380.2C516MD4.33KS525*	II	IP54	33	H07RN-F 5G2,5	230V~/16A 400V~/16A	1800W 4150W	3600W 11kW	14.92
275 20 555 000	GT 380.2C516MD4.50PU515*	II	IP54	50	H07BQ-F 5G1,5	230V~/16A 400V~/16A	1250W 3000W	3600W 11kW	11.72
275 20 563 000	GT 380.2C516MD4.33PU525*	II	IP54	33	H07BQ-F 5G2,5	230V~/16A 400V~/16A	1800W 4150W	3600W 11kW	12.52

















GT 450.516



- with 2 CEE sockets, 4-pin + E, 16A, 400V
- with 1 CEE socket, 2-pin + E, 16A, 230V
- with 2 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
280 50 000 000	GT 450.516					230V~/16A 400V~/16A			6.17
280 50 455 000	GT 450.516.50KS515*	II	IP54	50	H07RN-F 5G1,5	230V~/16A 400V~/16A	1250W 3000W	3600W 11kW	16.77
280 50 462 000	GT 450.516.25KS525*	II	IP54	25	H07RN-F 5G2,5	230V~/16A 400V~/16A	2500W 6580W	3600W 11kW	13.87
280 50 465 000	GT 450.516.50KS525*	II	IP54	50	H07RN-F 5G2,5	230V~/16A 400V~/16A	1800W 4850W	3600W 11kW	21.67
280 50 565 000	GT 450.516.50PU525*	II	IP54	50	H07BQ-F 5G2,5	230V~/16A 400V~/16A	1800W 4850W	3600W 11kW	18.17















HT 305.C516MD3



- with 1 CEE socket, 4-pin + E, 16A, 400V
- with 3 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
333 18 000 000	HT 305.C516MD3					230V~/16A 400V~/16A			4.41
333 18 452 000	HT 305.C516MD3.25KS515	I	IP54	25	H07RN-F 5G1,5	230V~/16A 400V~/16A	1500W 2000W	3600W 11kW	10.70
333 18 462 000	HT 305.C516MD3.25KS525	I	IP54	25	H07RN-F 5G2,5	230V~/16A 400V~/16A	1900W 2200W	3600W 11kW	12.20
333 18 463 000	HT 305.C516MD3.33KS525	I	IP54	33	H07RN-F 5G2,5	230V~/16A 400V~/16A	1700W 2000W	3600W 11kW	13.63













HT 305.2C516MD1



- with 2 CEE sockets, 4-pin + E, 16A, 400V
- with 1 earthed machine socket, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
333 21 000 000	HT 305.2C516MD1					230V~/16A 400V~/16A			3.70
333 21 452 000	HT 305.2C516MD1.25KS515	I	IP54	25	H07RN-F 5G1,5	230V~/16A 400V~/16A	1500W 2000W	3600W 11kW	9.92
333 21 462 000	HT 305.2C516MD1.25KS525	I	IP54	25	H07RN-F 5G2,5	230V~/16A 400V~/16A	1900W 2200W	3600W 11kW	12.22
333 21 463 000	HT 305.2C516MD1.33KS525	I	IP54	33	H07RN-F 5G2,5	230V~/16A 400V~/16A	1700W 2000W	3600W 11kW	13.60













HT 380.C516MD3



- with 1 CEE socket, 4-pin + E, 16A, 400V
- with 3 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
360 18 000 000	HT 380.C516MD3					230V~/16A 400V~/16A			5.64
360 18 452 000	HT 380.C516MD3.25KS515	I	IP40	25	H07RN-F 5G1,5	230V~/16A 400V~/16A	1800W 2000W	3600W 11kW	11.04
360 18 455 000	HT 380.C516MD3.50KS515	I	IP40	50	H07RN-F 5G1,5	230V~/16A 400V~/16A	1300W 1800W	3600W 11kW	16.24
360 18 462 000	HT 380.C516MD3.25KS525	I	IP40	25	H07RN-F 5G2,5	230V~/16A 400V~/16A	1800W 2200W	3600W 11kW	13.34
360 18 463 000	HT 380.C516MD3.33KS525	ı	IP40	33	H07RN-F 5G2,5	230V~/16A 400V~/16A	1800W 2000W	3600W 11kW	15.84









HT 380.2C516



- with 2 CEE sockets, 4-pin + E, 16A, 400V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
360 09 000 000	HT 380.2C516					400V~/16A			5.52
360 09 462 000	HT 380.2C516.25KS525	- 1	IP40	25	H07RN-F 5G2,5	400V~/16A	2200W	11kW	13.22
360 09 463 000	HT 380.2C516.33KS525	I	IP40	33	H07RN-F 5G2,5	400V~/16A	2000W	11kW	16.30













HT 380.2C516MD1



- with 2 CEE sockets 4-pin + E, 16A, 400V
- with 1 earthed machine socket 2-pin + E, 16A, 230V
- with self-closing hinged cover
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
360 21 000 000	HT 380.2C516MD1					230V~/16A 400V~/16A			5.62
360 21 452 000	HT 380.2C516MD1.25KS515	ı	IP40	25	H07RN-F 5G1,5	230V~/16A 400V~/16A	1800W 2000W	3600W 11kW	10.72
360 21 455 000	HT 380.2C516MD1.50KS515	I	IP40	50	H07RN-F 5G1,5	230V~/16A 400V~/16A	1300W 1800W	3600W 11kW	15.72
360 21 462 000	HT 380.2C516MD1.25KS525	I	IP40	25	H07RN-F 5G2,5	230V~/16A 400V~/16A	1800W 2200W	3600W 11kW	13.98
360 21 463 000	HT 380.2C516MD1.33KS525	I	IP40	33	H07RN-F 5G2,5	230V~/16A 400V~/16A	1800W 2000W	3600W 11kW	15.52















- with 1 CEE socket 4-pin + E, 16A, 400V
- with 3 earthed machine sockets 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
368 81 000 000	HT 385.C516MD3					230V~/16A 400V~/16A			6.64
368 81 465 000	HT 385.C516MD3.50KS525	I	IP40	50	H07RN-F 5G2,5	230V~/16A 400V~/16A	1500W 1800W	3600W 11kW	21.80













HT 385.2C516MD1



- with 2 CEE sockets, 4-pin + E, 16A, 400V
- with 1 earthed machine socket, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- · with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
368 21 000 000	HT 385.2C516MD1					230V~/16A 400V~/16A			5.92
368 21 465 000	HT 385.2C516MD1.50KS525	I	IP40	50	H07RN-F 5G2,5	230V~/16A 400V~/16A	1500W 1800W	3600W 11kW	21.80

HT 480.C516MD3













- with 1 CEE socket, 4-pin + E, 16A, 400V
- with 3 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
370 18 000 000	HT 480.C516MD3					230V~/16A 400V~/16A			7.66
370 18 465 000	HT 480.C516MD3.50KS525	I	IP40	50	H07RN-F 5G2,5	230V~/16A 400V~/16A	1500W 2000W	3600W 11kW	23.16











HT 480.2C516



- with 2 CEE sockets, 4-pin + E, 16A, 400V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
370 09 000 000	HT 480.2C516					400V~/16A			8.16
370 09 462 000	HT 480.2C516.25KS525	I	IP40	25	H07RN-F 5G2,5	400V~/16A	2500W	11kW	16.00
370 09 465 000	HT 480.2C516.50KS525	I	IP40	50	H07RN-F 5G2,5	400V~/16A	2000W	11kW	22.88











HT 480.2C516MD1



- with 2 CEE sockets, 4-pin + E, 16A, 400V
- with 1 earthed machine socket, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
370 21 000 000	HT 480.2C516MD1					230V~/16A 400V~/16A			10.76
370 21 465 000	HT 480.2C516MD1.50KS525	I	IP40	50	H07RN-F 5G2,5	230V~/16A 400V~/16A	1500W 2000W	3600W 11kW	25.91
370 21 475 000	HT 480.2C516MD1.50KS540	I	IP40	50	H07RN-F 5G4,0	230V~/16A 400V~/16A	1500W 2000W	3600W 11kW	28.92











HT 582.C516MD3



- with 1 CEE socket 4-pin + E, 16A, 400V
- with 3 earthed machine sockets 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
379 18 000 000	HT 582.C516MD3					230V~/16A 400V~/16A			12.92

400V 16A CEE sockets resistant to pressurised water Special rubber













GT 380.2CW516WS2



- suitable for wet areas
- with 2 CEE sockets which are resistant to pressurised water, 4-pin + E, 16A, 400V
- with 2 earthed sockets which are resistant to pressurised water, 2-pin + E, 16A, 230V
- with bayonet closure
- with thermal protection
- with locking brake screw
- when fitted with cable, includes plug which is resistant to pressurised water at the end
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
275 35 000 000	GT 380.2CW516WS2					230V~/16A 400V~/16A			4.88
275 35 455 000	GT 380.2CW516WS2.50KS515*	II	IP55	50	H07RN-F 5G1,5	230V~/16A 400V~/16A	1250W 3000W	3600W 11kW	15.48
275 35 463 000	GT 380.2CW516WS2.33KS525*	II	IP55	33	H07RN-F 5G2,5	230V~/16A 400V~/16A	1800W 4150W	3600W 11kW	15.08
275 35 555 000	GT 380.2CW516WS2.50PU515*	II	IP55	50	H07BQ-F 5G1,5	230V~/16A 400V~/16A	1250W 3000W	3600W 11kW	11.88
275 35 563 000	GT 380.2CW516WS2.33PU525*	II	IP55	33	H07BQ-F 5G2,5	230V~/16A 400V~/16A	1800W 4150W	3600W 11kW	12.68

400V 16A Special rubber



















GT 450.FI.516



- with residual current device, 25A / 30mA, 0.03sec
- with 2 CEE sockets, 4-pin + E, 16A, 400V
- with 1 CEE socket, 2-pin + E, 16A, 230V
- with 2 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- with 1 automatic fuse, 3-pole, 16A
- with automatic fuse, 1-pole, 16A
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
280 54 000 000	GT 450.Fl.516					230V~/16A 400V~/16A			7.42
280 54 462 000	GT 450.Fl.516.25KS525*	II	IP54	25	H07RN-F 5G2,5	230V~/16A 400V~/16A	2500W 6580W	3600W 11kW	15.12
280 54 465 000	GT 450.FI.516.50KS525	II	IP54	50	H07RN-F 5G2,5	230V~/16A 400V~/16A	1800W 4850W	3600W 11kW	22.92
280 54 562 000	GT 450.Fl.516.25PU525*	II	IP54	25	H07BQ-F 5G2,5	230V~/16A 400V~/16A	2500W 6580W	3600W 11kW	13.82
280 54 565 000	GT 450.Fl.516.50PU525*	II	IP54	50	H07BQ-F 5G2,5	230V~/16A 400V~/16A	1800W 4850W	3600W 11kW	19.42

400V 16A Special rubber



















GT 450.FID.516



- with residual current device, 25A / 30mA, 0.03sec
- with 3 CEE sockets which are resistant to pressurised water, 4-pin + E, 16A, 400V
- with 2 earthed machine sockets which are resistant to pressurised water, 2-pin + E, 16A, 230V
- with bayonet closure
- with thermal protection
- with locking brake screw
- with 1 automatic fuse, 3-pole, 16A
- with 1 automatic fuse, 1-pole, 16A
- when fitted with cable, includes plug which is resistant to pressurised water at the end of the cable
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
280 60 000 000	GT 450.FID.516					230V~/16A 400V~/16A			7.41
280 60 465 000	GT 450.FID.516.50KS525*	II	IP55	50	H07RN-F 5G2,5	230V~/16A 400V~/16A	1800W 4850W	3600W 11kW	22.91

400V 16A Residual current device Special rubber















HT 482.FI.C516MD3



- with residual current device, 25A / 30mA, 0.03sec
- with 1 CEE socket, 4-pin + E, 16A, 400V
- with 3 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
376 18 000 000	HT 482.FI.C516MD3					230V~/16A 400V~/16A			10.80
376 18 462 000	HT 482.FI.C516MD3.25K\$525	I	IP40	25	H07RN-F 5G2,5	230V~/16A 400V~/16A	2000W 3000W	3600W 22kW	17.45
376 18 465 000	HT 482.FI.C516MD3.50KS525	I	IP40	50	H07RN-F5G2,5	230V~/16A 400V~/16A	2000W 3000W	3600W 22kW	25.95















GT 380.LED



- special rubber cable drum with 2 LED lights each 75W + on/off switch
- with 2 CEE sockets, 4-pin + E, 16A, 400V
- with 2 earthed machine sockets, 2-pin + E, 16A
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
275 49 452 000	GT 380.LED.2C516MD2.25KS515*	II	IP54	25	H07RN-F 5G1,5	230V~/16A 400V~/16A	1800W 4150W	3600W 11kW	11.31
275 49 455 000	GT 380.LED.2C516MD2.50KS515*	II	IP54	50	H07RN-F 5G1,5	230V~/16A 400V~/16A	1250W 3000W	3600W 11kW	16.62
275 49 552 000	GT 380.LED.2C516MD2.25PU515*	II	IP54	25	H07BQ-F 5G1,5	230V~/16A 400V~/16A	1800W 4150W	3600W 11kW	9.51
275 49 555 000	GT 380.LED.2C516MD2.50PU515*	II	IP54	50	H07BQ-F 5G1,5	230V~/16A 400V~/16A	1250W 3000W	3600W 11kW	13.02

400V 16A Flat slip ring Plastic



IT 300K.MS5



- slip ring drum with double contacting
- with 5-pole flat slip ring, 16A
- with 1,5 m H05RR-F 3G1.5 connection cable
- with steel tube handle
- with locking brake screw

Order No.	Item	Cable type	Version	Weight (kg)
260 32 000 000	IT 300K.MS5		5-pole slip ring, 16A	3.06

400V 16A
Flat slip ring
Special rubbe





GT 450.MS5



- slip ring drum with double contacting
- with 5-pole flat slip ring, 16A
- with 1,5 m H07RN-F 5G1.5 connection cable
- with thermal protection
- with locking brake screw

Order No.	Item	Cable type	Version	Weight (kg)
280 32 000 000	GT 450.MS5		5-pole slip ring, 16A	7.00

400V 16A Flat slip ring Sheet steel



HT 582.MS5



- slip ring drum with double contacting
- with 5-pole flat slip ring 16A
- with 1,5 m connection cable H07RN-F 51,5
- with locking brake screw

Order No.	Item	Cable type	Version	Weight (kg)
379 32 000 000	HT 582.MS5		5-pole slip ring, 16A	13.09

400V 16A
Flachschleifring





SK 4822.MS5.16



- slip ring drum with double contacting
- stackable construction cable drum
- with 5-pole slip ring, 16A
- with locking brake screw

Order No.	Item	Cable type	Version	Weight (kg)
432 33 000 000	SK 4822.MS5.16		5-pole slip ring, 16A	17.50



HT 381.MS10



- slip ring drum with double contacting
- with 10-pole flat slip ring 16A
- without connection cable
- with locking brake screw

Order No.	Item	Cable type	Version	Weight (kg)
362 33 000 000	HT 381.MS10		10-pole slip ring 16A	6.36

HT 481.MS10



- slip ring drum with double contacting
- with 10-pole flat slip ring 16A
- without connection cable
- with locking brake screw

Order No.	Item	Cable type	Version	Weight (kg)
372 33 000 000	HT 481.MS10		with 10-pole slip ring 16A	8.37

400V 25A Brush slip ring Sheet steel



SK 4822.MS5.25



- slip ring drum with double-contacting
- with 5 high-quality 25A brush slip rings
- stackable construction cable drum
- with locking brake screw

Order No.	Item	Cable type	Version	Weight (kg)
432 32 000 000	SK 4822.MS5.25		5-pole slip ring, 25A	17.90



SK 4823.MS5.25/40



- slip ring drum with double contacting
- with high-quality 25A-40A brush slip rings
- stackable construction cable drum
- with locking brake screw

Order No.	Item	Cable type	Version	Weight (kg)
433 32 000 000	SK 4823.MS5.25/40		5-pole slip ring, 25A-40A	18.90

400V 32A CEE sockets Special rubber



















GT 380.C532C516MD2



- with 1 CEE socket, 4-pin + E, 32A, 400V
- with 1 CEE socket, 4-pin + E, 16A, 400V
- with 2 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- 1 contactor, 4-pole, 40A, 400V
- with thermal protection
- with locking brake screw
- 1 automatic fuse, 3-pole, 16A
- 1 automatic fuse, 1-pole, 16A
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
275 26 000 000	GT 380.C532C516MD2					230V~/16A 400V~/16A 400V~/32A			5.70
275 26 475 000	GT 380.C532C516MD2.25KS540*	II	IP54	25	H07RN-F 5G4,0	230V~/16A 400V~/16A 400V~/32A	2500W 6000W 6000W	3600W 11kW 22kW	16.70
275 26 473 000	GT 380.C532C516MD2.33KS540*	II	IP54	33	H07RN-F 5G4,0	230V~/16A 400V~/16A 400V~/32A	2500W 6000W 6000W	3600W 11kW 22kW	19.90





















GT 450.532



- with 1 CEE socket, 4-pin + E, 32A, 400V
- with 1 CEE socket, 4-pin + E, 16A, 400V
- with 1 CEE socket, 2-pin + E, 16A, 230V
- with 2 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- 1 contactor, 4-pole, 40A, 400V
- with thermal protection
- with locking brake screw
- 1 automatic fuse, 3-pole, 16A
- 1 automatic fuse, 1-pole, 16A
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
280 52 000 000	GT 450.532					230V~/16A 400V~/16A 400V~/32A			7.15
280 52 472 000	GT 450.532.25KS540*	II	IP54	25	H07RN-F 5G4,0	230V~/16A 400V~/16A 400V~/32A	2500W 6000W 6000W	3600W 11kW 22kW	18.15
280 52 473 000	GT 450.532.33KS540*	II	IP54	33	H07RN-F 5G4,0	230V~/16A 400V~/16A 400V~/32A	2500W 6000W 6000W	3600W 11kW 22kW	21.35
280 52 482 000	GT 450.532.25KS560*	II	IP54	25	H07RN-F 5G6,0	230V~/16A 400V~/16A 400V~/32A	2500W 6000W 6000W	3600W 11kW 22kW	21.55













HT 381.C532MD2



- with 1 CEE socket, 4-pin + E, 32A, 400V
- with 2 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
362 19 000 000	HT 381.C532MD2					230V~/16A 400V~/32A			6.12
362 19 472 000	HT 381.C532MD2.25KS540	I	IP40	25	H07RN-F 5G4,0	230V~/16A 400V~/32A	3000W 4000W	3600W 22kW	17.12
362 19 473 000	HT 381.C532MD2.33KS540	I	IP40	33	H07RN-F 5G4,0	230V~/16A 400V~/32A	2750W 3000W	3600W 22kW	20.32











HT 381.2C532



- with 2 CEE sockets, 4-pin + E, 32A, 400V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
362 10 000 000	HT 381.2C532					400V~/32A			6.28
362 10 472 000	HT 381.2C532.25KS540	T.	IP40	25	H07RN-F 5G4,0	400V~/32A	4000W	22kW	17.28
362 10 473 000	HT 381.2C532.33KS540	I	IP40	33	H07RN-F 5G4,0	400V~/32A	3000W	22kW	20.60













HT 381.2C532MD1



- with 2 CEE sockets, 4-pin + E, 32A, 400V
- with 1 earthed machine socket, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
362 22 000 000	HT 381.2C532MD1					230V~/16A 400V~/32A			6.93
362 22 472 000	HT 381.2C532MD1.25KS540	I	IP40	25	H07RN-F 5G4,0	230V~/16A 400V~/32A	3000W 3500W	11kW 22kW	17.93















HT 381.C532C516MD1



- with 1 CEE socket, 4-pin + E, 32A, 400V
- with 1 CEE socket, 4-pin + E, 16A, 400V
- with 1 earthed machine socket, 2-pin + E, 16A, 230V
- with self-closing hinged cover
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
362 30 000 000	HT 381.C532C516MD1					230V~/16A 400V~/16A 400V~/32A			6.26
362 30 472 000	HT 381.C532C516MD1.25KS540	l	IP40	25	H07RN-F 5G4,0	230V~/16A 400V~/16A 400V~/32A	3000W 3500W 3500W	3600W 11kW 22kW	17.26













HT 481.C532MD2



- with 1 CEE socket, 4-pin + E, 32A, 400V
- with 2 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
372 19 000 000	HT 481.C532MD2					230V~/16A 400V~/32A			8.21
372 19 475 000	HT 481.C532MD2.50KS540	I	IP40	50	H07RN-F 5G4,0	230V~/16A 400V~/32A	2000W 3500W	3600W 22kW	30.01

HT 481.2C532











- with 2 CEE sockets, 4-pin + E, 32A, 400V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
372 10 000 000	HT 481.2C532					400V~/32A			8.38
372 10 475 000	HT 481.2C532.50KS540	I	IP40	50	H07RN-F 5G4,0	400V~/32A	3500W	22kW	30.18
372 10 482 000	HT 481.2C532.25KS560	I	IP40	25	H07RN-F 5G6,0	400V~/32A	6000W	22kW	24.00













HT 481.2C532MD1



- with 2 CEE sockets, 4-pin + E, 32A, 400V
- with 1 earthed machine socket, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
372 22 000 000	HT 481.2C532MD1					230V~/16A 400V~/32A			8.43
372 22 475 000	HT 481.2C532MD1.50KS540	I	IP40	50	H07RN-F 5G4,0	230V~/16A 400V~/32A	2100W 3600W	3600W 22kW	30.23













HT 481.C532C516MD1



- with 1 CEE socket, 4-pin + E, 32A, 400V
- with 1 CEE socket, 4-pin + E, 16A, 400V
- with 1 earthed machine socket, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
372 30 000 000	HT 481.C532C516MD1					230V~/16A 400V~/16A 400V~/32A			8.35
372 30 475 000	HT 481.C532C516MD1.50KS540	l	IP40	50	H07RN-F 5G4,0	230V~/16A 400V~/16A 400V~/32A	2000W 3500W 3500W	3600W 11kW 22kW	30.15











HT 582.C532MD2



- with 1 CEE socket 4-pin + E, 32A, 400V
- with 2 earthed machine sockets 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
379 19 000 000	HT 582.C532MD2					230V~/16A 400V~/32A			12.32

400V 32A Special rubber





















GT 450.FI.532



- with residual current device, 40A / 30mA, 0.03sec
- with 1 CEE socket, 4-pin + E, 32A, 400V
- with 1 CEE socket, 4-pin + E, 16A, 400V
- with 1 CEE socket, 2-pin + E, 16A, 230V
- with 2 earthed machine sockets, 2-pin + E, 16A, 230V
- with self-closing hinged covers
- with thermal protection
- with locking brake screw
- 1 automatic fuse, 3-pole, 16A
- 1 automatic fuse, 1-pole, 16A
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
280 56 000 000	GT 450.FI.532					230V~/16A 400V~/16A 400V~/32A			7.44
280 56 472 000	GT 450.FI.532.25KS540*	II	IP54	25	H07RN-F 5G4,0	230V~/16A 400V~/16A 400V~/32A	2500W 6000W 6000W	3600W 11kW 22kW	18.44
280 56 473 000	GT 450.FI.532.33KS540*	II	IP54	33	H07RN-F 5G4,0	230V~/16A 400V~/16A 400V~/ 32A	2500W 6000W 6000W	3600W 11KW 22KW	21.64
280 56 482 000	GT 450.FI.532.25KS560*	II	IP54	25	H07RN-F 5G6,0	230V~/16A 400V~/16A 400V~/32A	2500W 6000W 6000W	3600W 11kW 22kW	21.84

400V 32A Special rubber



GT 450.FID.532





















- with residual current device, 25A / 30mA, 0.03sec
- with 1 CEE socket which is resistant to pressurised water, 4-pin + E, 32A, 400V (IP67)
- with 2 CEE sockets which are resistant to pressurised water, 4-pin + E, 16A, 400V (IP67)
- with 2 earthed machine sockets which are resistant to pressurised water, 2-pin + E, 16A, 230V (IP68)
- with thermal protection
- with locking brake screw
- 1 automatic fuse, 3-pole, 16A
- 1 automatic fuse, 1-pole, 16A
- complies with the requirements of the German Social Accident Insurance (DGUV), DGUV Info 203-006 (BGI 608) and DGUV Info 203-005 (BGI 600 Category K2)*

Order no.	Item	Degree of protection	Protection- class	Cable (m)	Cable type	Nominal voltage	Cable power Coiled	Cable power Uncoiled	Weight (kg)
280 62 000 000	GT 450.FID.532					230V~/16A 400V~/16A 400V~/32A			7.52
280 62 472 000	GT 450.FID.532.25KS540*	II	IP55	25	H07RN-F 5G4,0	230V~/16A 400V~/16A 400V~/32A	2500W 6000W 6000W	3600W 11KW 22KW	18.52
280 62 473 000	GT 450.FID.532.33KS540*	II	IP55	33	H07RN-F 5G4,0	230V~/16A 400V~/16A 400V~/32A	2500W 6000W 6000W	3600W 11KW 22KW	21.72
280 62 482 000	GT 450.FID.532.25KS560*	II	IP55	25	H07RN-F 5G6,0	230V~/16A 400V~/16A 400V~/32A	2500W 6000W 6000W	3600W 11KW 22KW	21.92



Travelling column unit for models HT 380 - HT 582



A practical accessory for use in all kinds of places. Convenient handling, robust design.

Retrofittable, separate travelling column consisting of stable steel tube frame, black powder coating with particularly impact-proof and abrasion-proof surface. With two solid rubber wheels, Ø 140 mm. The cable drums are simply hooked into the angle on the sliding tube with the handle and they centre themselves automatically. Designed for absolutely safe transport.

Order No.	Item	Version	Weight (kg)
397 00 000 000	Travelling column unit	for HT 380 - HT 582	4.00



Patented cable rewind for GT 310 model



Plastic attachment kit. Suitable for cable diameters from approx. 6 to 14 mm. This patented cable holder ensures that the cable no longer has to be guided by hand during winding. The cable rewind performs this task masterfully and automatically places the cable on the drum core "layer by layer" during winding. This ensures that the capacity of the cable drum is always is used to its full extent. Can be retrofitted for all GT 310 models.

Order No.	Item	Version	Weight (kg)
270 99 000 000	Cable rewind	for GT 310	0.23



Travelling unit for GT 380 and GT 450 models



Retrofittable attachment kit made from plastic with high shock resistance. With height-adjustable steel tube handle. With 2 polyamide wheels, ø 140 mm . Easy mounting on drum handle, stable and safe transport.

Order No.	Item	Version	Weight (kg)
397 00 010 000	Travelling unit	for GT 380 and GT 450	2.50



Transport trolley for the SK 310 - SK 450 series



A practical accessory for use in all kinds of places. With 4 steerable wheels. Wheel diameter 100 mm, solid rubber tyres. Corners of the plate protected, mould cavity for SK 310 - SK 450.

Order No.	Item	Version	Weight (kg)
405 99 000 000	TW SK-310-380-450	without brake	10.80

Transport trolley for SK 47 / SK 48 series



A practical accessory for use in all kinds of places. Convenient handling, stable design consisting of angle iron with black powder-coated surface, particularly impact-proof and abrasion-proof. With 2 steering castors and 2 fixed castors, solid rubber tyres, wheel diameter 100 mm, 5 model with brake (2 wheels with stop fix).

Order No.	Item	Version	Weight (kg)
432 99 000 000	TW 4700/4822	without brake	10.00
432 99 001 000	TW 4700/4822.S	with brake	10.00
433 99 000 000	TW 4701/4823	without brake	11.00
433 99 001 000	TW 4701/4823.S	with brake	11.00



EFT 130



- 3-pole flat slip ring, 10A for protected installation and attachment
- fuse connection terminal with 10A glass fuse
- without cover for connection housing
- without locking mechanism

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
681 00 303 000	EFT 130.3KK3075	IP20	3	H03VV-F 3G0,75	FT 150 Typ 1	230V~/10A	1000W	2300W	0.80

IP20

EFT 160



- 3-pole flat slip ring, 10A for protected installation and attachment
- fuse connection terminal with 10A glass fuse
- cover for connection housing
- without locking mechanism

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
671 00 305 000	EFT 160.5KK3075	IP20	5	H03VV-F 3G0,75	FT 150 Typ 1	230V~/10A	1000W	2300W	0.89
671 00 304 000	EFT 160.4KK310	IP20	4	H05VV-F 3G1,0	FT 150 Typ 1	230V~/10A	1250W	2300W	1.00



EFT 265



- 3-pole flat slip ring, 16A
- for protected installation and attachment
- fuse connection terminal with 10A glass fuse
- cover for connection housing
- without locking mechanism

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
661 00 308 000	EFT 265.0308	IP20	8	H05VV-F 3G1,5	FT 260 Typ 2	230V~/10A	1800W	2300W	2.29

IP20

EFT 130A



- 3-pole flat slip ring, 10A
- for protected installation and attachment
- fuse connection terminal with 10A glass fuse
- without cover for connection housing
- locking mechanism

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
681 01 303 000	EFT 130A.3KK3075	IP20	3	H03VV-F 3G0,75	FT 150 Typ 1	230V~/10A	1000W	2300W	0.80



EFT 160A



- 3-pole flat slip ring, 10A for protected installation and attachment
- fuse connection terminal with 10A glass fuse
- cover for connection housing
- locking mechanism

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
671 01 305 000	EFT 160A.5KK3075	IP20	5	H03VV-F 3G0,75	FT 150 Typ 1	230V~/10A	1000W	2300W	1.08
671 01 304 000	EFT 160A.4KK310	IP20	4	H05VV-F 3G1,0	FT 150 Typ 1	230V~/10A	1250W	2300W	1.00

IP20

EFT 265A



- 3-pole flat slip ring, 16A
- for protected installation and attachment
- fuse connection terminal with 10A glass fuse
- cover for connection housing
- locking mechanism

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
661 01 308 000	EFT 265A.0308	IP20	8	H05VV-F 3G1,5	FT 260 Typ 2	230V~/10A	1800W	2300W	2.90



FT 150



- 3-pole flat slip ring, 10A fuse connection terminal with 10A glass fuse
- universal holder for ceiling/wall mounting
- locking mechanism which can be deactivated

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
670 00 305 000	FT 150.5KK3075	IP20	5	H03VV-F 3G0,75	FT 150 Typ 1	230V~/10A	1000W	2300W	1.18
670 00 304 000	FT 150.4KK310	IP20	4	H05VV-F 3G1,0	FT 150 Typ 1	230V~/10A	1250W	2300W	1.35





FT 260



- 3-pole flat slip ring, 16A
- fuse connection terminal with 10A glass fuse
- universal holder for ceiling/wall mounting
- locking mechanism which can be deactivated

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
640 00 300 000	FT 260.0300				FT 260 Typ 2	230V~/10A			2.23
640 00 308 000	FT 260.0308	IP20	8	H05VV-F 3G1,5	FT 260 Typ 2	230V~/10A	1800W	2300W	3.00
640 00 312 000	FT 260.0312	IP20	12	H05VV-F 3G1,0	FT 260 Typ 2	230V~/10A	1000W	2300W	3.10









- 3-pole flat slip ring, 16A fuse connection terminal with 10A glass fuse
- pivoting wall holder
- rotating ceiling holder as accessory available locking mechanism which can be deactivated
- without plug connection

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
660 00 300 000	FT 350.0300				FT 350 Typ 1	230V~/10A			4.51
660 00 315 000	FT 350.0315	IP20	15	H07RN-F 3G1,5	FT 350 Typ 1	230V~/10A	1800W	2300W	7.85

10A Flat slip ring, 5-pole Plastic



IP20

EFT 265



- 5-pole flat slip ring, 16A
- for protected installation and attachment
- fuse connection terminal with 10A glass fuse
- cover for connection housing
- without locking mechanism

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
661 00 505 000	EFT 265.0505	IP20	5	H05VV-F 5G1,5	FT 260 Typ 2	400V~/10A	2200W	6800W	2.98

IP20

EFT 265A



- 5-pole flat slip ring, 16A
- for protected installation and attachment
- fuse connection terminal with 10A glass fuse
- cover for connection housing
- locking mechanism

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
661 01 505 000	EFT 265A.0505	IP20	5	H05VV-F 5G1,5	FT 260 Typ 2	400V~/10A	2200W	6800W	3.10









- 5-pole flat slip ring, 16A
- fuse connection terminal with 10A glass fuse
- universal holder for ceiling/wall mounting
- locking mechanism which can be deactivated

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
640 00 500 000	FT 260.0500				FT 260 Typ 2	400V~/10A			2.58
640 00 505 000	FT 260.0505	IP20	5	H05VV-F 5G1,5	FT 260 Typ 2	400V~/10A	2200W	6800W	2.80







- 5-pole flat slip ring, 16A
- fuse connection terminal with 10A glass fuse
- pivoting wall holder
- rotating ceiling holder as accessory available
- locking mechanism which can be deactivated
- without plug connection

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
660 00 500 000	FT 350.0500				FT 350 Typ 1	400V~/10A			5.51
660 00 510 000	FT 350.0510	IP20	10	H07RN-F 5G1,5	FT 350 Typ 1	400V~/10A	2400W	6800W	8.05







FT 038 without thermoswitch



- 3-pole flat slip ring, 16A
- locking mechanism which can be deactivated
- without thermoswitch
- pivoting wall holder
- rotating ceiling holder as accessory available

Note:

A H07RN-F or H07BQ-F cable is required for use outdoors and in damp rooms.

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 31 300 000	FT 038.0300.16				FT 038 Typ 2	230V~/16A			9.12
620 31 320 000	FT 038.0320	IP44	20	H07RN-F 3G1,5	FT 038 Typ 2	230V~/16A	1000W	2300W	12.30



FT 038 with thermoswitch



- 3-pole flat slip ring 16A
- locking mechanism which can be deactivated
- thermoswitch
- pivoting wall holder
- rotating ceiling holder as accessory available

Note:

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 31 325 000	FT 038.0325.16	IP44	25	H05BQ-F 3G1,0	FT 038 Typ 3	230V~/16A	800W	2300W	10.12
620 31 325 001	FT 038.0325.16	IP44	15	H07RN-F 3G2,5	FT 038 Typ 3	230V~/16A	2000W	3800W	12.27









- 5-pole flat slip ring 16A locking mechanism
- flange fastening
- pivoting wall and rotating ceiling holder as accessories available

Note:

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
630 31 723 000	FT 046.0300.16				FT 046 Typ 3	230V~/16A			20.80
630 31 423 000	FT 046.0333	IP44	33	H07RN-F 3G1,5	FT 046 Typ 3	230V~/16A	800W	3600W	27.14
630 31 325 000	FT 046.0325.16	IP44	25	H07RN-F 3G2,5	FT 046 Typ 3	230V~/16A	2000W	3600W	29.33









- 5-pole flat slip ring, 16A locking mechanism which can be deactivated
- pivoting wall holder
- rotating ceiling holder as accessory available

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 32 500 000	FT 038.0500.16				FT 038 Typ 2	400V~/16A			8.42
620 32 515 000	FT 038.0515	IP44	15	H07RN-F 5G1,5	FT 038 Typ 2	400V~/16A	4000W	11kW	12.75
620 32 525 400	FT 038.0525.16	IP44	15	H07RN-F 5G2,5	FT 038 Typ 2	400V~/16A	4500W	11kW	14.32









- 5-pole flat slip ring 16A locking mechanism
- flange fastening
- pivoting wall and rotating ceiling holder as accessories available

Note:

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
630 32 753 000	FT 046.0500.16				FT 046 Typ 2	400V~/16A			21.50
630 32 453 000	FT 046.0530	IP44	30	H07RN-F 5G1,5	FT 046 Typ 2	400V~/16A	3800W	11kW	28.00

16A







FT 038



- 7-pole flat slip ring, 16A locking mechanism which can be deactivated
- cable Ölflex Crane with supporting element
- pivoting wall holder
- rotating ceiling holder as accessory available

Note:

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 33 715 900	FT 038.0700				FT 038 Typ 1				10.00
620 33 715 000	FT 038.0715	IP44	15	Ölflex 7G1,5	FT 038 Typ 1	400V~/16A	4000W	11kW	15.06
620 33 715 400	FT 038.0715	IP44	15	Ölflex 7G2,5	FT 038 Typ 1	400V~/16A	4000W	11kW	17.06









- 7-pole flat slip ring 16A locking mechanism
- cable Ölflex Crane with supporting element
- flange fastening
- pivoting wall and rotating ceiling holder as accessories avilable

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
630 33 792 000	FT 046.0700.16				FT 046 Typ 1	400V~/16A			24.00
630 33 492 000	FT 046.0725	IP44	25	Ölflex 7G1,5	FT 046 Typ 1	400V~/16A	3800W	11kW	30.00

16A Flat slip ring, 10-pole





FT 038



- 10-pole flat slip ring 16A
- locking mechanism which can be deactivated
- cable Ölflex Classic
- pivoting wall holder
- rotating ceiling holder as accessory available

Note:

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 10 000 000	FT 038.1000				FT 038 Typ 2	400V~/16A			11.00
620 10 010 000	FT 038.1010	IP44	10	Ölflex 10G1,5	FT 038 Typ 2	400V~/16A	4200W	11kW	13.68





FT 046



- 10-pole flat slip ring, 16A looking mechanism
- cable Ölflex Classic
- flange fastening
- pivoting wall and rotating ceiling holder as accessories available

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
630 10 000 400	FT 046.1000				FT 046 Typ 2	400V~/16A			20.00
630 20 025 400	FT 046.1020	IP44	20	Ölflex 10G1,5	FT 046 Typ 2	400V~/16A	3800W	11kW	20.00

16A Flat slip ring, 15-pole





FT 038



- 15-pole flat slip ring 16A
- looking mechanism
- flange fastening
- pivoting wall and rotating ceiling holder as accessories available

Notes:

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 15 000 000	FT 038.1500				FT 038 Typ 1	400V~/16A			12.00







FT 038



- 20-pole flat slip ring 16A locking mechanism which can be deactivated
- pivoting wall holder
- rotating ceiling holder as accessory available

Note:

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 20 000 000	FT 038.2000				FT 038 Typ 1	400V~/16A			18.51
620 20 015 000	FT 038.2015	IP44	15	Ölflex 20G1,0	FT 038 Typ 1	400V~/16A	4000W	11kW	17.51

16A Flat slip ring, 20-pole Sheet steel





FT 046



- 20-pole flat slip ring 16A
- looking mechanism
- flange fastening
- pivoting wall and rotating ceiling holder as accessories available

Notes:

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
630 20 000 000	FT 046.2000				FT 046 Typ 2	400V~/16A			24.00
630 20 025 000	FT 046.2025	IP44	25	Ölflex 20G1,0	FT 046 Typ 2	400V~/16A	3800W	11kW	33.00







FT 038



- for higher power ratings 3-pole brush slip ring 25A
- locking mechanism which can be deactivated
- pivoting wall holder rotating ceiling holder as accessory available

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
621 31 300 000	FT 038.0300.25				FT 038 Typ 2	230V~/25A			12.51
621 31 325 000	FT 038.0325.25	IP44	15	H07RN-F 3G2,5	FT 038 Typ 2	230V~/25A	2000W	4500W	16.13

25A Brush slip ring, 3-pole Sheet steel







FT 046



- for higher power ratings
- 3-pole brush slip ring 25A
- locking mechanism and flange fastening
- pivoting wall and rotating ceiling holder as accessories available

Note:

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
631 31 300 000	FT 046.0300.25				FT 046 Typ 2	230V~/25A			22.33
631 31 325 000	FT 046.0325.25	IP44	25	H07RN-F 3G2,5	FT 046 Typ 2	230V~/25A	2000W	3600W	29.33







FT 038



- for higher power ratings 5-pole brush slip ring 25A
- locking mechanism which can be deactivated
- pivoting wall holder rotating ceiling holder as accessory available

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
621 32 500 000	FT 038.0500.25				FT 038 Typ 1	400V~/25A			13.30
621 32 525 000	FT 038.0525.25	IP44	15	H07RN-F 5G2,5	FT 038 Typ 1	400V~/25A	4500W	11kW	18.00

25A Brush slip ring, 5-pole Shoot stool







FT 046



- for higher power ratings
- 5-pole brush slip ring 25A
- locking mechanism which can be deactivated
- pivoting wall and rotating ceiling holder as accessory available

Note:

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
631 32 500 000	FT 046.0500.25				FT 046 Typ 2	400V~/25A			24.33
631 32 525 000	FT 046.0525.25	IP44	25	H07RN-F 5G2,5	FT 046 Typ 2	400V~/25A	4000W	11kW	33.33







FT 038 ceiling holder



- for higher power ratings
- 5-pole brush slip ring 40A
- locking mechanism which can be deactivated
- · ceiling holder

Note:

A H07RN-F or H07BQ-F cable is required for use outdoors and in damp rooms.

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
622 32 500 000	FT 038.0500.40-DB				FT 038 Typ 1	400V~/40A			14.96
622 32 515 000	FT 038.0515.40-DB	IP44	15	H07RN-F 5G4,0	FT 038 Typ 1	400V~/40A	6500W	22kW	19.16

FT 038 wall holder







- for higher power ratings
- 5-pole brush slip ring 40A
- locking mechanism which can be deactivated
- pivoting wall holder

Note

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
622 32 500 001	FT 038.0500.40-WB				FT 038 Typ 1	400V~/40A			14.96
622 32 515 001	FT 038.0515.40-WB	IP44	15	H07RN-F 5G4,0	FT 038 Typ 1	400V~/40A	6500W	22kW	21.34

40A Brush slip ring, 5-pole Sheet steel







FT 046



- for higher power ratings
- 5-pole brush slip ring 40A
- locking mechanism and flange fastening
- pivoting wall and rotating ceiling holder as accessories available

Note:

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
632 32 500 000	FT 046.0500.40				FT 046 Typ 1	400V~/40A			27.02
632 32 520 000	FT 046.0520.40	IP44	20	H07RN-F 5G4,0	FT 046 Typ 1	400V~/40A	6500W	22kW	36.33

with attachments
10A
Plug connection
Plactic



IP20

FT 150



- 3-pole flat slip ring 10A
- fuse connection terminal with 10A glass fuse
- universal holder for ceiling/wall mounting
- locking mechanism which can be deactivated
- plug connection (right-angle Schuko plug and Schuko coupling)

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
670 10 304 000	FT 150.4KK310.S316	IP20	4	H05VV-F 3G1,0	FT 150 Typ 1	230V~/10A	1250W	2300W	1.67

IP20



- 3-pole flat slip ring 16A
- fuse connection terminal with 10A glass fuse
- universal holder for ceiling/wall mounting
- locking mechanism which can be deactivated
- plug connection (right-angle Schuko plug and Schuko coupling)

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
640 10 308 000	FT 260.0308.S316	IP20	8	H05VV-F 3G1,5	FT 260 Typ 2	230V~/10A	1800W	2300W	3.66
640 10 312 000	FT 260.0312.S316	IP20	12	H05VV-F 3G1,0	FT 260 Typ 2	230V~/10A	1000W	2300W	3.82

with attachments 10A Plug connection Plastic



IP20

FT 260.0305-cube MD4



- 3-pole flat slip ring 16A
- fuse connection terminal with 10A glass fuse
- universal holder for ceiling/wall mounting
- locking mechanism which can be deactivated
- 2 cable stoppers
- power cube with 4 Schuko sockets

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
640 00 305 500	FT 260.0305-Cube MD4	IP20	5	H05VV-F 3G2,5	FT 260 Typ 1	230V~/10A	1800W	2300W	3.00



FT 350.0315.S316



- 3-pole flat slip ring 16A
- fuse connection terminal with 10A glass fuse
- pivoting wall holder
- rotating ceiling holder as accessory available
- · locking mechanism which can be deactivated
- plug connection (Schuko plug and Schuko coupling)

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
660 10 315 000	FT 350.0315.S316	IP20	15	H07RN-F 3G1,5	FT 350 Typ 1	230V~/10A	1800W	2300W	7.85

with attachments
10A
Plug connection



IP20

FT 350.0510.C516



- 5-pole flat slip ring 16A
- fuse connection terminal with 10A glass fuse
- pivoting wall holder
- rotating ceiling holder as accessory available
- locking mechanism which can be deactivated
- plug connection (CEE plug and coupling 16A)

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
660 10 510 000	FT 350.0510.C516	IP20	10	H07RN-F 5G1,5	FT 350 Typ 1	400V~/10A	2400W	6800W	9.32

with attachments
16A
Plug connection
Plactic





FT 038



- 3-pole flat slip ring 16A
- locking mechanism which can be deactivated
- pivoting wall holder
- rotating ceiling holder as accessory available
- plug connection (Schuko plug and Schuko coupling)

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 31 320 503	FT 038.0320.S316	IP44	15	H07RN-F 3G2,5	FT 038 Typ 2	230V~/16A	1000W	2300W	12.30
620 31 320 502	FT 038.0320.S316	IP44	20	H07RN-F 3G1,5	FT 038 Typ 2	230V~/16A	1000W	2300W	12.30



FT 038.0515.C516



- 5-pole flat slip ring 16A
- locking mechanism which can be deactivated
- pivoting wall holder
- rotating ceiling holder as accessory available
- plug connection (CEE plug and coupling 16A)

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 10 515 000	FT 038.0515.C516	IP44	15	H07RN-F 5G1,5	FT 038 Typ 2	400V~/16A	4000W	11kW	12.75



Earthing drums



- for earthing purposes
- earthing clamp universal holder for FT 260 series
- ceiling holder as accessory as of model FTE 350 optionally available
- locking mechanism which can be deactivated
- cable color H07V-K: yellow/green cable color H07RN-F: black

Order No.	item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
641 00 110 000	FTE 260.0110.H07VK		10	H07V-K 1x10	FT 260 Typ 2				3.46
641 00 210 000	FTE 260.0110.H07RN		8	H07RN-F 1x10	FT 260 Typ 2				4.02
641 00 206 000	FTE 260.0616.H07VK		10	H07V-K 1x16	FT 260 Typ 2				3.46
660 00 115 000	FTE 350.0115.H07VK		15	H07V-K 1x10	FT 350 Typ 1				7.00
660 00 215 000	FTE 350.0115.H07RN		15	H07RN-F 1x10	FT 350 Typ 1				7.69
660 00 214 000	FTE 350.1416.H07VK		14	H07V-K 1x16	FT 350 Typ 1				7.00
660 00 210 000	FTE 350.0110.H07RN		10	H07RN-F 1x16	FT 350 Typ 1				7.69
620 31 120 000	FTE 038.0120.H07VK		20	H07V-K 1x10	FT 038 Typ 2				10.25
620 31 220 000	FTE 038.0120.H07RN		20	H07RN-F 1x10	FT 038 Typ 2				11.07
620 31 120 400	FTE 038.0120.H07VK		20	H07V-K 1x16	FT 038 Typ 2				10.25
620 31 220 400	FTE 038.0120.H07RN		18	H07RN-F 1x16	FT 038 Typ 2				11.07
630 31 230 000	FTE 046.3016.H07VK		30	H07V-K 1x16	FT 046 Typ 3				27.00
630 31 130 400	FTE 046.0130.H07RN		30	H07RN-F-1x16	FT 046 Typ 3				27.00

for data networks 16A Plug connection Plastic







FT 038.1205-LAN-cube MD3NEW



- 5-pole slip ring16A
- data slip ring
- data transmission: 1 GBits/Ethernet
- application: 100BASE-TX
- 8 m extension cable Hybrid
- power cube with 3 machine sockets and RJ45 plug
- 2 m cable for permanent connection
- looking device can be turned off
- wall bracket for pivoted mounting
- rotating ceiling holder as accessory available

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 06 000 400	FT 038.1205.LAN-Cube MD3	IP20	8		FT 038 Typ 2	230V~/16A	1000W	3680W	9.47



IP20

FT 150-LANNEW



- data slip ring
- data transmission: 1GBits/s Ethernet
- application: 100BASE-TX
- 5 m extension cable with RJ45 plug; cable color blue
- RJ45 socket for connection lead
- locking device can be turned off
- without cable connection
- · universal holder for wall/ceiling mounting

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
670 00 125 000	FT 150.1205.LAN	IP20	5		FT 150 Typ 1				1.35



FT 260-LANNEW



- data slip ring
- data transmission: 1GBits/s Ethernet
- application: 100BASE-TX
- 10 m extension cable with RJ45 plug; cable color blue
- RJ45 socket for connection lead
- · locking device can be turned off
- without cable connection
- universal holder for wall/ceiling mounting

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
640 00 121 000	FT 260.1210.LAN	IP20	10		FT 260 Typ 2				2.23

for eMobility 16A without electronics Plastic



IP42

FT 260.0416.E00.0520.0103-0000NEW



- cable reel for eMobility
- 4-pole flat slip ring
- locking mechanism which can be deactivated
- thermal protection
- 5 m extension cable (3G2,5+1x0,5 qmm) with type 2 charging socket 16A
- 1,5 m connecting cable (3G2,5+1x0,5 qmm) with type 2 charging connector 16A (on request also for direct connection without plug)
- universal holder for wall or ceiling mounting

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
640 90 405 000	FT 260.0416.E00.0520.0103-0000	IP42	5	3G2,5+1x0,5qmm	FT 260 Typ 2	230V~/16A	2200W	3600W	4.43



FT 350.0416.E00.0820.0103-0000NEW



- cable reel for eMobility
- 4-pole flat slip ring
- · locking mechanism which can be deactivated
- thermal protection
- 8 m extension cable (3G2,5+1x0,5 qmm) with type 2 charging socket 16A
- 1,5 m connecting cable (3G2,5+1x0,5 qmm) with type 2 charging connector 16A (on request also for direct connection without plug)
- swivel wall mounting bracket
- rotating ceiling holder as accessory available

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
660 90 412 000	FT 350.0416.E00.0820.0103-0000	IP42	8	3G2,5+1x0,5qmm	FT 350 Typ 1	230V~/16A	3600W	3600W	7.82

for eMobility 16A without electronics Plastic



IP42

FT 350.0616.E00.0820.0203-0000NEW



- cable reel for eMobility
- 6-pole flat slip ring
- locking mechanism which can be deactivated
- thermal protection
- 8 m charging cable (5G2,5+1x0,5 qmm) with type 2 charging socket 16A
- 1,5 m connecting cable (5G2,5+1x0,5 qmm) with type 2 charging connector 16A (on request also for direct connection without plug)
- siwvel wall mounting bracket
- rotating ceiling holder as accessory available

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
660 90 610 000	FT 350.0616.E00.0820.0203- 0000	IP42	8	5G2,5+1x0,5qmm	FT 350 Typ 1	400V~/16A	4200W	11kW	8.87



FT 038.0616.E00.0820.0203-0000NEW



- cable reel for eMobility
- 6-pole flat slip ring
- axle with ball bearings
- locking mechanism which can be deactivated
- thermal protection
- 8 m extension cable (5G2,5+1x0,5 qmm) with type 2 charging socket 16A
- 1,5 m connection cable (5G2,5+1x0,5 qmm) with type 2 charging connector 16A (on request also for direct connection without plug)
- swivel wall mounting bracket
- rotating ceiling holder as accessory available

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 90 615 000	FT 038.0616.E00.0820.0203-0000	IP44	8	5G2,5+1x0,5qmm	FT 038 Typ 2	400V~/16A	11kW	11kW	13.36

for eMobility 32A without electronics Plastic





FT 038.1032.E00.0820.0304-0000NEW



- cable reel for eMobility
- 10-pole flat slip ring
- axle with ball bearings
- locking mechanism which can be deactivated
- 8 m extension cable (5G6,0+1x0,5 qmm) with type 2 charging socket 32A
- 1,5 m connection cable (5G6,0+1x0,5 qmm) with type 2 charging connector 32A (on request also for direct connection without plug)
- swivel wall mounting bracket
- rotating ceiling holder as accessory available

Order No.	Item	Protection class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 90 010 000	FT 038.1032.E00.0820.0304- 0000	IP44	8	5G6,0+1x0,5qmm	FT 038 Typ 1	400V~/32A	22kW	22kW	15.36

for eMobility 16A with electronics Plastic







FT 260.0416.I02.0520.0101-0000NEW



- · cable reel for eMobility
- 4-pole flat slip ring
- integrated charging electronics
- thermal protection
- locking mechanism which can be deactivated
- 5 m extension cable (3G2,5+1x0,5 qmm) with type 2 charging socket 16A
- 2 m connecting cable H07RN-F 3G2,5 without plug connection
- · universal holder for wall or ceiling mounting

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
640 91 405 000	FT 260.0416.I02.0520.0101-0000	IP42	5	3G2,5+1x0,5qmm	FT 260 Typ 2	230V~/16A	2200W	3600W	4.43





FT 350.0416.I02.0820.0101-0000NEW



- cable reel for eMobility
- 4-pole flat slip ring
- integrated charging electronics
- thermal protection
- locking mechanism which can be deactivated
- 8 m extension cable (3G2,5+1x0,5 qmm) with type 2 charging socket 16A
- 2 m connecting cable H07RN-F 3G2,5 without plug connection
- swivel wall mounting bracket
- rotating ceiling holder as accessory available

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
660 91 405 000	FT 350.0416.I02.0820.0101- 0000	IP42	8	3G2,5+1x0,5qmm	FT 350 Typ 1	230V~/16A	2200W	3600W	8.87

for eMobility 16A with electronics Plastic





FT 038.0516.I02.0820.0205-0000NEW



- cable reel for eMobility
- 5-pole flat slip ring
- integrated charging electronics
- thermal protection
- axle with ball bearings
- locking mechanism which can be deactivated
- 8 m extension cable (5G2,5+1x0,5 qmm) with type 2 charging socket 16A
- 2 m connection cable H07RN-F 5G2,5 without connection plug
- swivel wall mounting bracket
- rotating ceiling holder as accessory available

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 91 615 000	FT 038.0616.102.0820.0205-0000	IP44	8	5G2,5+1x0,5qmm	FT 046 Typ 2	400V~/16A	11kW	11kW	12.75



FT 038.0516.I03.0820.0205-0000NEW



- cable reel for eMobility
- 5-pole flat slip ring
- integrated charging electronics
- thermal protection
- axle with ball bearings
- DC residual current sensor 6mA
- locking mechanism which can be deactivated
- 8 m extension cable (5G2,5+1x0,5 qmm) with type 2 charging socket
- 2 m connection cable H07RN-F 5G2,5 without plug connection
- swivel wall mounting bracket
- rotating ceiling holder as accessory available

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 92 615 000	FT 038.0616.I03.0820.0205-0000	IP40	8	5G2,5+1x0,5qmm	FT 046 Typ 2	400V~/16A	11kW	11kW	12.75

for signal transmission 2A Data slip ring, 6-pole





- 6-pole data slip ring
- for signal transfer up to 230V max. 2A per ring
- terminals in the distribution box
- locking device can be turned off
- without connection and pull out cable
- pivoting wall holder
- rotating ceiling holder as accessory available

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 06 000 000	FT 038.0600				FT 038 Typ 3				8.00







- 12-pole data slip ring for signal transfer up to 230V max. 2A per ring
- terminals in the distribution box
- locking device can be turned off
- without connection and pull out cable
- pivoting wall holder
- rotating ceiling holder as accessory available

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 12 000 000	FT 038.1200				FT 038 Typ 2				8.00







- 12-pole data slip ring
- for signal transfer up to 230V max. 2A per ring terminals in the distribution box
- locking device can be turned off
- without connection and pull out cable
- pivoting wall holder
- rotating ceiling holder as accessory available

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
630 12 000 000	FT 046.1200				FT 046 Typ 3				20.00







- 18-pole data slip ring for signal transfer up to 230V max. 2A per ring
- terminals in the distribution box
- locking device can be turned off
- without connection and pull out cable
- pivoting wall holder
- rotating ceiling holder as accessory available

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 18 000 000	FT 038.1800				FT 038 Typ 1				8.00







- 18-pole data slip ring
- for signal transfer up to 230V max. 2A per ring terminals in the distribution box
- locking device can be turned off
- without connection and pull out cable
- pivoting wall holder
- rotating ceiling holder as accessory available

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
630 18 000 000	FT 046.1800				FT 046 Typ 2				20.00

for signal transmission 2A Data slip ring, 24-pole







- 24-pole data slip ring
- for signal transfer up to 230V max. 2A per ring
- terminals in the distribution box
- locking device can be turned off
- without connection and pull out cable
- pivoting wall holder
- rotating ceiling holder as accessory available

Order No.	Item	Protec- tion class	Cable (m)	Cable type	Spring pack	Nominal voltage	Cable power coiled	Cable power uncoiled	Weight (kg)
620 24 000 000	FT 038.2400				FT 038 Typ 1				8.00



EST 160



- for attachment to work benches, etc.
- operating pressure: 10 barair connection: R 1/4" external
- without locking mechanism

Order No.	Item	Tube	Hose	Operating pressure (bar)	Spring pack	Weight (kg)
663 04 030 000	EST 160.0403	3 m NW4	R 1/4" external		FT 150 Typ 1	1.28

EST 265



- for attachment to work benches, etc.
- operating pressure: 10 bar
- air connection: R 1/4" external
- without locking mechanism

Order No.	Item	Tube	Hose	Operating pressure (bar)	Spring pack	Weight (kg)
664 06 080 000	EST 265.0608	6,5 m NW6	R 1/4" external		FT 260 Typ 2	3.02



EST 160A



- for attachment to work benches, etc.
- operating pressure: 10 bar
- air connection: R 1/4" external
- with locking mechanism (A)

Order No.	Item	Tube	Hose	Operating pressure (bar)	Spring pack	Weight (kg)
663 04 031 000	EST 160A.0403	3 m NW4	R 1/4" external		FT 150 Typ 1	1.28

EST 265A



- for attachment to work benches, etc.
- operating pressure: 10 bar
- air connection: R 1/4" external
- with locking mechanism (A)

Order No.	Item	Tube	Hose	Operating pressure (bar)	Spring pack	Weight (kg)
664 06 081 000	EST 265A.0608	6,5 m NW6	R 1/4" external		FT 260 Typ 2	3.02



ST 150



- operating pressure: 10 bar
- air connection: R 1/4" external
- locking mechanism which can be deactivated
- universal holder for wall and ceiling mounting

Order No.	Item	Tube	Hose	Operating pressure (bar)	Spring pack	Weight (kg)
635 04 030 000	ST 150	3 m NW4	R 1/4" external		FT 150 Typ 1	1.28



- operating pressure: 10 bar
- air connection: R 1/4" external
- locking mechanism which can be deactivated
- universal holder for wall and ceiling mounting

Order No.	Item	Tube	Hose	Operating pressure (bar)	Spring pack	Weight (kg)
645 06 080 000	ST 260	6,5 m NW6	R 1/4" external		FT 260 Typ 2	2.44

Hose reel **Operating pressure:** 10-15 bar Nennweite: Material:





- operating pressure: 15 bar air connection: R 1/4" external locking mechanism which can be deactivated
- pivoting wall holder
- rotating ceiling holder as accessory available

Order No.	Item	Tube	Hose	Operating pressure (bar)	Spring pack	Weight (kg)
665 06 100 000	ST 350.0610	10 m NW6	R 1/4" external		FT 350 Typ 1	7.37





- operating pressure: 15 bar connection for supply line: R 1/2" locking mechanism which can be deactivated
- pivoting wall holder
- rotating ceiling holder as accessory available

Order No.	Item	Tube	Hose	Operating pressure (bar)	Spring pack	Weight (kg)
625 09 120 000	ST 038.0912	12 m NW9	R 3/8" internal		FT 038 Typ 2	13.12
625 06 150 000	ST 038.0615	15 m NW6	R 1/4" internal		FT 038 Typ 2	12.51
625 13 090 000	ST 038.1309	9 m NW13	R 1/2" internal		FT 038 Typ 2	11.62





- operating pressure: 15 bar connection for supply line: R 1/2"
- locking mechanism
- flange fastening
- rotating ceiling holder and pivoting wall holder as accessories

Order No.	Item	Tube	Hose	Operating pressure (bar)	Spring pack	Weight (kg)
635 06 250 000	ST 046.0625	25 m NW6	R 1/4" internal		FT 046 Typ 3	27.09
635 09 200 000	ST 046.0920	20 m NW9	R 3/8" internal		FT 046 Typ 3	28.16
635 13 150 000	ST 046.1315	15 m NW13	R 1/2" internal		FT 046 Typ 2	28.98



ST 038HD.1010



- operating pressure: 180 bar
- connection for supply line: M16x1.5 internal
- locking mechanism which can be deactivated
- pivoting wall holder
- rotating ceiling holder as accessory available

Order No.	Item	Tube	Hose	Operating pressure (bar)	Spring pack	Weight (kg)
626 09 100 000	ST 038HD.1010	10 m NW10	M16x1,5 internal		FT 038 Typ 1	13.12

ST 038HD.0615



- operating pressure: 225 bar
- connection for supply line: M16x1.5 internal
- locking mechanism which can be deactivated
- pivoting wall holder
- rotating ceiling holder as accessory available

Order No.	Item	Tube	Hose	Operating pressure (bar)	Spring pack	Weight (kg)
626 06 150 000	ST 038HD.0615	15 m NW6	M16x1,5 internal		FT 038 Typ 1	13.12



ST 046HD.1015



- operating pressure: 225 bar
- connection for supply line: M16x1.5 internal
- flange fastening and locking mechanism
- rotating ceiling holder and pivoting wall all holder as accessories available

Order No.	Item	Tube	Hose	Operating pressure (bar)	Spring pack	Weight (kg)
636 09 150 000	ST 046HD.1015	15 m NW10	M16x1,5 internal		FT 046 Typ 1	26.00

ST 046HD.0620



- operating pressure: 225 bar
- flange fastening and locking mechanism
- connection for supply line: M16x1.5 internal
- rotating ceiling/wall holder as accessory available

Order No.	Item	Tube	Hose	Operating pressure (bar)	Spring pack	Weight (kg)
636 06 200 000	ST 046HD.0620	20 m NW6	M16x1,5 internal		FT 046 Typ 1	28.00



Roller guides



Stand-alone roller yoke for easy cable guidance in the case of long working distances. The roller guide should be installed in places where the cable would run over edges. This helps to prevent excessive wear and a reduction in spring-back force. The roller guide is to be fastened in place with two M6 screws (hole spacing 59,9 mm). Defl ection of the extension cable by an angle of 90° or more is to be avoided.

Order No.	Item	Version	Weight (kg)
600 00 010 000	Roller guides		0.20

Mounted plug connections...



Only in conjunction with cable reels.

Order No.	Item	Version		Weight (kg)
91 020 000	Insertion connection S 316	Earthed plug and coupling		0.12
91 045 000	Insertion connection C316	CEE-plug and -socket	2-pole + E, 16A, 230V	0.40
91 050 000	Insertion connection C516	CEE-plug and coupling	4-pole+E, 16A, 400V	0.40
91 060 000	Insertion connection C532	CEE-plug and coupling	4-pole+E, 32A, 400V	0.54
91 070 000	Suspended cpupling 3/316	Earthed plug with 3x suspended	coupling (not for FT 50)	0.60



Ceiling holder for FT 350 - FT 046



Order No.	Item	Version	Weight (kg)
600 00 040 000	DB 350	FT 350, swivel range 360°	0.70
600 00 020 000	DB 038	FT 038, rotates 360°	0.40
600 00 050 000	DB 046	FT 046, rotates 360°	2.80

Wall holder for FT 350 - FT 046



Order No.	Item	Version	Weight (kg)
600 00 060 000	WB 046	FT/ST 046, pivots 88°	2.80
600 00 030 000	WB 038/350	FT/ST 038/350, pivots 88°	1.04



Roller guide for hoses



Stand-alone roller yoke for easy hose guidance in the case of long working distances. The roller guide should be installed in places where hoses would run over edges. This helps to prevent excessive wear and a reduction in spring-back force. The roller guide is to be fastened in place with two M6 screws (hole spacing 2.36 inch). Defl ection of the extension hose by an angle of 90° or more is to be avoided.

Order No.	Item	Version	Weight (kg)
600 00 010 000	Roller guides		0.20

Blow gun with quick coupling for ST 260 - ST 038



Order No.	Item	Version		Weight (kg)
98 900 000	Blow gun	ST 260 with quick-release coupling		0.26
98 910 000	Blow gun	ST 350, ST 038	with quick-release coupling	0.26



Ceiling holder for ST 350 - ST 046



Order No.	Item	Version	Weight (kg)
600 00 040 000	DB 350	FT 350, swivel range 360°	0.70
600 00 020 000	DB 038	FT 038, rotates 360°	0.40
600 00 050 000	DB 046	FT 046, rotates 360°	2.80

Wall holder for ST 350 - ST 046



Order No.	Item	Version	Weight (kg)
600 00 060 000	WB 046	FT/ST 046, pivots 88°	2.80
600 00 030 000	WB 038/350	FT/ST 038/350, pivots 88°	1.04

Distribution



Worldwide

Audio/Video & Broadcast Kinovox Scandinavia Marielundvej 45B 2730 Herlev

DENMARK

Phone: +45 (0) 70 22 38 11 E-Mail: info@kinovox.dk www.kinovox.dk

Trade & Industry

Nord Tech Industrisystemer

Lucernemarken 18 A 5260 Odense S **DENMARK**

Phone: +45 (0) 65 91 98 02 E-Mail: post@nord-tech.dk www.nord-tech.dk

Audio/Video & Broadcast

Helipilt Ltd. Estonia

Tänassilma Vetevana tee 6-3 76406 Harjumaa **ESTONIA**

Phone: +372 (0) 56 220 102 E-Mail: helipilt@gmail.com

www.helipilt.ee

Trade & Industry Oy T. Stenbacka AB

Emalikatu 2 B 04440 Järvenpää **FINLAND**

Phone: +358 (0) 207 432 320 E-Mail: info@stenbacka.fi www.t-stenbacka.fi

Audio/Video & Broadcast

Sommer Cable France

115 Rue de la république 67720 Weyersheim

FRANCE

Phone: +33 (0) 388 51 87 34 E-Mail: france@sommercable.com

www.sommercable.fr

Trade & Industry **Cablecaddy**

Unit 11 Crystal Business Centre Sandwich, Kent CT13 9QX

GREAT BRITAIN

Phone: +44 (0) 1304 612957 E-Mail: info@cablecaddy.co.uk www.marcaddy.com

Trade & Industry

Hensel Electric India Pvt.Ltd.

35 Kunnam Village Sunguvarchathram - Walajabad Road 4th km behind Samsung / Flextronics Sriperumbudur Taluk Kanchipuram Dist. - 631 604 Tamil Nadu

INDIA

Phone: +91 (0) 44 3727 0202 E-Mail: info@hensel-electric.in

www hensel in

Trade & Industry

Reykjafell Ltd.

Skipholti 35 105 Reykjavik

ISLAND

Phone: +354 (0) 588 6000 E-Mail: reykjafell@reykjafell.is

www.reykjafell.de

Trade & Industry

Electrosen Ltd.

Manufacture & Marketing of Electrical Appliances 23, Hapalmach St.

Bnei-Brak 51118 ISRAEL

Phone: +972 (0) 3 618 41 31 E-Mail: info@electrosen.co.il www.electrosen.co.il

Audio/Video & Broadcast

Link srl

Via Bruno Pontecorvo 10

00012 Guidonia Montecelio (Rome)

ITALY

Phone: +39 (0) 06 227251 E-Mail: info@linkitaly.com www.linkitaly.com