

VIDAFLEX S350 UL

Composition

VIDAFLEX S350: Silicone elastomer coated knitted "E"- glass insulating sleeving.

VIDAFLEX S350 insulating sleeveings offer a high degree of flexibility and they provide a good resistance against ozone, ultraviolet radiation and humidity.

VIDAFLEX S350 are UL recognized components (UL-File: E154100(M)).

VIDAFLEX S350 insulating sleeveings are compliant to the requirements of the directive 2002/95/EC (RoHS).

Max. short term temperature: 250°C.

Application

Protection and insulation of leads and wiring harness in household appliances, lamps and vehicles.

Insulation of the internal wiring of electrical motors.

Thermal Class 180 (Class H) according to IEC 60085

Bore size (mm)	Nom. wall thickness (mm)	Weight approx. (g/m)	Breakthrough voltage at RT (kV)
3,0 ± 0,15	1,0	12	≥ 7,0
4,0 ± 0,2	1,0	16	≥ 7,0
5,0 ± 0,2	1,0	19	≥ 7,0
6,0 ± 0,25	1,0	22	≥ 7,0
7,0 ± 0,25	1,0	25	≥ 7,0
8,0 ± 0,25	1,0	29	≥ 7,0
9,0 ± 0,3	1,0	33	≥ 7,0
10,0 ± 0,3	1,0	37	≥ 7,0
12,0 ± 0,3	1,0	44	≥ 7,0
14,0 ± 0,4	1,0	53	≥ 7,0
16,0 ± 0,4	1,0	64	≥ 7,0
18,0 ± 0,5	1,0	75	≥ 7,0
20,0 ± 0,5	1,0	88	≥ 7,0
22,0 ± 0,5	1,0	105	≥ 7,0
24,0 ± 0,5	1,0	116	≥ 7,0
25,0 ± 0,5	1,4	122	≥ 7,0
Measurement according to EN 60684-2			
Availability			
Standard roll length	250, 100, 50 and 25 m spools, dependant on bore size. Cut to length on request.		
Colour	Black		

All values stated are to be seen as typical values. We reserve the right to introduce changes within the framework of further technical development. We do not accept any obligations or liabilities in respect of this information. Status: 01/2009
 KREMPPEL GmbH · Papierfabrikstrasse 4 · D-71665 Vaihingen / Enz · Tel. +49 (0) 7042 915-0 · E-mail: info@krempel-group.com